Welch WOB-L Piston Vacuum/Pressure Pumps

Simplicity is the key to the design of the WOB-L piston pumps. As the piston wobbles, air resistance on the upward stroke expands the PTFE seal on the piston to increase efficiency while compensating for the wobble action. WOB-L pumps set the industry standard for efficient vacuum utility. Use these pumps for reliable and affordable vacuum/pressure in applications where corrosion resistance is not required. WOB-L piston pumps come accessorised as standard including pressure and vacuum gauges & regulators, inlet catch pot and exhaust silencer. All pumps are supplied with a carrying handle for easy portability. Suitable for use with aqueous fumes including buffers. Not recommended for pumping acidic, basic, or organic fumes.

- Analytically pure, oil free vacuum
- User friendly
- Lightweight and portable
- Fully accessorised

- Compact design
- Suction cup feet for stability
- Designed for permanent operation

Code	Alt Ref	Description	Delivery, L/ min	Ultimate Vacuum, mbar	Max Overpressure, mbar	Price
PUM1074	2522C-02	2522 WOB-L piston pump	18	133	7.9	£591.00
PUM1076	2534C-02	2534 WOB-L piston pump	28	93	5.8	£597.00
PUM1128	2546C-02	2546 WOB-L piston pump	38	80	5.2	£825.00

Welch CRVpro Vacuum Pumps

Provides a reduced risk of chemical attacks and oil breakdown by diluting aggressive chemicals with a larger oil chamber. Its cool running characteristic also reduces corrosion. Additionally a chemical resistant coating protects the stationary components. Furthermore the CRVpro enables extended oil change intervals for less maintenance costs. Less oil consumption is a result of the cool operation and the extended usability of oil.

Description

CRVpro 2

CRVpro 4

CRVpro 6

CRVpro 8

CRVpro 16

CRVpro 24

CRVpro 30

Description

DirecTorr premium vacuum oil

DirecTorr premium vacuum oil

Stainless steel vacuum hose DN 16

Stainless steel vacuum hose DN 25

FOM16 Oil mist filter with oil drainback

FOM25 Oil mist filter with oil drainback

- Coated oil case to slow metal corrosion
- DN 16 KF inlet/exhaust flanges (DN 25 KF for CRVpro 16, 24, 30)

Alt Ref

3022-00

3042-00

3062-00

3082-00

3162-00

3242-00

3302-00

800995-01

800995-05

710755

710756

700621

700622

- Anti-suck back valve
- I ow noise level

Code

PUM1006

PUM4616

PUM4618

PUM4620

PI1M4622

PUM4652

PUM4654

Code

PUM4628

PUM4634

PUM4636

PUM4638

PUM1008

PUM1012

Accessories

Forced oil lubrication

Gas ballast valve to allow pumping of condensable vapours

WELCH

Supplied with Welch Director Premium Oil (1L for CRVpro2, 2L for CRVpro4, 6, 8, and 3L for CRVpro16, 24,30)

mbar

7 x 10⁻²

7 x 10⁻²

7 x 10⁻²

7 x 10⁻²

6 x 10⁻³

6 x 10⁻³

6 x 10⁻³

Pack

1500mm

1500mm

Each

Each

1L

51

Ultimate Vacuum,

mbar

2 x 10⁻³

2 x 10⁻³

2 x 10⁻³

2 x 10⁻³

3 x 10⁻³

 3×10^{-3}

 3×10^{-3}



£2993.00

£3176.00

£4211.00

£4908.00

Price

£26.40

£111.00

£143.00

£155.00

£282.00

£363.00

823



WELCH