

BACK **2** BASICS

— 2024

EXCLUSIVE offers on essentials for your laboratory

25% OFF

Eppendorf
ThermoMixer® C



**UP TO
69% OFF**

SLS Lab Pro
Variable Volume
Pipettes



30% OFF

OHAUS
Frontier® 5707
Multi Centrifuge



55% OFF

IKA
Lab Dancer
Vortex Mixer



50% OFF

Benchmark
Roto-Mini™
Plus Rotator



**UP TO
42% OFF**

SLS Lab Pro
Insulated Eco
Drying Cabinets



Valid 1st Jun - 30th Sept 2024



**SCIENTIFIC
LABORATORY
SUPPLIES**

BACK 2 BASICS 2024

WELCOME to our 2024 issue of **BACK 2 BASICS**, where we work closely with a number of our key suppliers to bring you the best deals in the market for selected laboratory products. In this issue, we have fantastic offers on selected lines from our own **SLS Lab Pro**, **SLS Select** and **SLS Lab Basics** brands alongside those from world renowned manufacturers such as **Grant**, **Eppendorf**, **Corning**, **Gilson**, **Mettler Toledo**, **OHAUS**, **IKA**, **Haier** and **Benchmark**.

To benefit from the prices offered in this brochure, please use the appropriate product code when placing your order.

These offers are **EXCLUSIVE** to SLS and valid until **30th Sept 2024**



Visit our website for supplementary 'B2B EXTRA' online offers for more great savings!

KEY PRODUCT SYMBOLS

1 YEAR Length of Warranty

NEW NEW Product

SUSTAINABLE AWARDS

Raw materials

Manufacturing

Distribution & packaging

Use

Disposal

For more information on our Sustainability Awards visit: scientificlabs.ie/sustainability

Buy One, Get One TREE

Look out for products with the 'Buy One, Get One TREE' icon in our promotions. With every purchase of these products, we will plant a tree on your behalf.

Working in partnership with **Ecologi**



Eppendorf MiniSpin®/MiniSpin® plus Mini Centrifuges

2 YEARS

eppendorf

Entry level centrifuges that are powerful and easy to use, but small enough so that each workstation can be equipped with a personal centrifuge. Optimal ventilation flow reduces heating and protects temperature sensitive samples, and automatic lid opening at the end of the run to prevent sample warming and to allow easy access to samples.

- Extremely compact footprint
- Acceleration and deceleration time <13s
- User-friendly digital display for time and speed
- Separate short spin key for fast and comfortable centrifugation
- Soft touch lid closure for ergonomic lid locking
- Large LCD display
- MiniSpin® plus provides automatic RPM/RCF conversion, and extended timer to 99 min or continuous centrifugation
- Supplied with rotor which has a capacity of 12 x 1.5/2.0mL tubes

25% OFF



Code	Description	Max Speed, RPM	Max RCF, x g	Dims, w x d x h, mm	List Price, €	Offer Price, €
B2B4904	MiniSpin®	800 to 13400	12100	225 x 230 x 130	1231.10	956.00
B2B4906	MiniSpin® plus	800 to 14500	14100	225 x 230 x 130	1599.00	1243.00

Eppendorf Pipette Kits

eppendorf

The Eppendorf Research® plus is one of the safest and most ergonomic mechanical pipettes available. Meeting the highest needs of precision and accuracy, this micropipette is remarkably light, both in terms of weight and pipetting forces, which helps you to avoid hand and arm strain.

Choose the Eppendorf Reference® 2 mechanical pipette with ergonomic single-button operation and benefit from its high precision and accuracy with reduced operating efforts. Its smooth surface and full autoclavability guarantee efficient decontamination - making it the ideal companion when working under sterile conditions.



Code	Supplied with	List Price, €	Offer Price, €
B2B1058	6 x Research® plus pipettes (0.1 - 2.5µL, 0.5 - 10µL, 2 - 20µL, 10 - 100µL, 20 - 200µL, 100 - 1000µL), Pipette Carousel 2, 6 x ep.T.I.P.S.® box 2.0 with 96 pipette tips and ballpoint pen	1699.00	1338.00
B2B1060	6 x Reference® 2 pipettes (0.1 - 2.5µL, 0.5 - 10µL, 2 - 20µL, 10 - 100µL, 20 - 200µL, 100 - 1000µL), Pipette Carousel 2, 6 x ep.T.I.P.S.® box 2.0 with 96 pipette tips and ballpoint pen	2179.00	1634.00

Eppendorf Combitips® advanced Positive Displacement Pipette Tips

eppendorf



**PURCHASE
8 PACKS AT YOUR
PRICE AND
RECEIVE A FREE
M4 MULTIPETTE
WORTH
€464!**

Optimise your workflows for accuracy and precision with Combitips® advanced dispenser tips. With an integrated piston, they function by the positive displacement principle and ensure that the correct volume of liquid is dispensed regardless of the physical properties. You can therefore achieve high-precision dispensing, independent of the flow characteristics of the liquid, and safely work with radioactive or toxic materials due to the hermetically sealed piston that prevents aerosol contamination.

- Dedicated consumable for all Multipette® multi-dispenser pipettes from Eppendorf
- 9 volume sizes offer a maximum range of dispensing volumes with individual colour coding for quick identification
- Eppendorf Quality purity grade
- Unique funnel geometry ensures comfortable handling while preventing damage to gloves



Code	Volume, mL	Colour Code	List Price, €
B2B1554	0.1	White	116.48
B2B1556	0.2	Light blue	116.48
B2B1558	0.5	Purple	116.48
B2B1560	1	Yellow	116.48
B2B1562	2	Green	116.48
B2B1564	5	Blue	116.48
B2B1566	10	Orange	116.48
B2B1568	25	Red	136.50
B2B1570	50	Light grey	152.10



Improve your Harvesting Efficiency

Eppendorf High-Speed Centrifuges: Your everyday solution supporting you in every step

In academia and pharma, handling diverse sample volumes poses challenges.

Whether your work requires harvesting of biomass in volumes of up to 6 L per run, pelleting of cells, subcellular organelles or larger viruses, or extraction, precipitation, concentration and purification of nucleic acids in up to 50 mL tubes, Eppendorf High-Speed Centrifuges are the optimal solution to support your everyday centrifugation tasks.

- > Centrifuge CR22N is the optimal solution for your everyday centrifugation tasks
- > Centrifuge CR30NX is our super-speed solution for a large variety of applications

Find out more:

www.scientificlabs.ie/eppendorf-highspeed-centrifuges

Eppendorf ThermoMixer® C

2 YEARS

eppendorf

Combines excellent mixing performance and temperature control to guarantee complete, dependable and reproducible test results.

- Mixing, heating, and cooling in one instrument for high flexibility
- All common vessels and plate formats from 5µL to 50mL by different Eppendorf SmartBlocks for standard applications
- Ideal for cell thawing when using Eppendorf SmartBlock cryo thaw
- Anti-spill technology prevents lid wetting and cross-contamination
- Increased mixing frequency of up to 3000rpm for effective sample mixing
- Excellent temperature management for maximum temperature accuracy, resulting in safe handling
- Compatible with Eppendorf ThermoTop® (condens.protect®) for condensation-free sample handling (for Eppendorf SmartBlocks up to 2.0mL)
- Predefined program keys and clearly arranged menu guides enable simple and intuitive operations
- Freely programmable program keys for individual optimisation
- Eppendorf PhysioCare Concept® provides ergonomic design and operation



25% OFF

SmartBlocks

Code	Description	Capacity	List Price, €	Offer Price, €
B2B1064	SmartBlock 0.5mL	24 x 0.5mL reaction vessels	733.20	550.00
B2B1066	SmartBlock 1.5mL	24 x 1.5mL reaction vessels	733.20	550.00
B2B1068	SmartBlock 2.0mL	24 x 2.0mL reaction vessels	733.20	550.00
B2B1070	SmartBlock 5mL	8 x 5.0mL Eppendorf tubes	733.20	550.00
B2B1072	SmartBlock 15mL	8 x 15mL conical tubes	733.20	550.00
B2B1074	SmartBlock 50mL	4 x 50mL conical tubes	733.20	550.00
B2B1076	SmartBlock Cryothaw	24 x 1.5 - 2mL cryotubes	733.20	550.00
B2B1078	SmartBlock 12mm	24 x 12mm Ø reaction vessels	910.00	683.00
B2B1080	SmartBlock Plates	Microplates and deepwell plates	910.00	683.00
B2B1082	SmartBlock PCR 96	96 well PCR plates	910.00	683.00
B2B1084	SmartBlock PCR 384	384 well PCR plates	910.00	683.00
B2B1086	SmartBlock DWP 500	Eppendorf deepwell plates 96/500µL	910.00	683.00
B2B1088	SmartBlock DWP 1000	Eppendorf deepwell plates 96/1000µL	910.00	683.00

Code	List Price, €	Offer Price, €
B2B1062	3532.10	2649.00

SLS Select Centrifuge Tubes



- Certified RNase and DNase free
- Sterile
- Manufactured from high clarity medical grade polypropylene
- Leak proof flat polypropylene cap
- Printed graduations and a large writing area for sample identifications
- Racked tubes are packaged in recyclable card racks
- Lot traceability



- RCF: 9000 (15 and 50mL tubes)
- Supplied in packs of 500

Code	Description	Volume, mL	List Price, €	Offer Price, €
B2B06192	Loose	15	318.50	51.00
B2B06194	Racked	15	356.20	56.00
B2B06196	Loose	50	352.30	60.00
B2B06198	Racked	50	367.90	72.00
B2B06200	Skirted, bagged	50	388.70	66.00



Meker Portable Burners



UP TO
70% OFF

Code	Description	List Price, €	Offer Price, €
B2B06102	Burner	118.30	69.00
B2B06104	Cartridge, 240g	24.28	7.28

Portwest® 2852 Standard Lab Coats

PORTWEST

- Concealed stud front for easy access
- Two lower patch pockets and a single chest pocket for ample storage
- Non shrinking to ensure that this style maintains its shape wash after wash
- Excellent dye retention, making the garment look newer for longer
- 65% polyester, 35% cotton
- Garment decoration with logo or embroidery available - please enquire




Code	Size	List Price, €	Offer Price, €
B2B8186	2X small	32.63	24.50
B2B8188	X small	32.63	24.50
B2B8190	Small	32.63	24.50
B2B8192	Medium	32.63	24.50
B2B8194	Large	32.63	24.50
B2B8196	X large	32.63	24.50
B2B8198	2X large	32.63	24.50
B2B8200	3X large	32.63	24.50
B2B8202	4X large	32.63	24.50
B2B8204	5X large	32.63	24.50

Swann-Morton Qlicksmart BladeFLASK Scalpel Blade Remover

A safe, quick and easy single-handed method for scalpel blade removal. The puncture proof sharps container shuts off automatically when it is full, and can be disposed of safely. Suitable for wall or surface mounting using the purpose designed bracket.



Code	Description	List Price, €	Offer Price, €
B2B06042	BladeFLASK scalpel blade remover	53.30	41.20
B2B06044	Mounting bracket	14.56	11.26



SLS Select Slides with Ground Edge, 76 x 26 x 1mm

Supplied in packs of 50

Code	Description	List Price, €
MIC2000	Plain	7.80
MIC2002	Twin frost	3.90

Unigloves® BioTouch Biodegradable Nitrile Gloves

UNIGLOVES®
KEEPING YOU SAFE



BioTouch contains a biodegradable technology that kickstarts a biodegradation process only when discarded in an active landfill environment, making these gloves more environmentally friendly with a much faster natural breakdown compared to regular nitrile.



- Latex, powder and phthalate free
- Beaded cuff, textured fingertips
- Length: 240 mm
- AQL 1.5
- Tested to ASTM D5511 and ASTM D5526 - 90% degradation in 490 days compared to regular nitrile
- EN ISO 374-1:2016 Type C K (chemical risks)
- EN 374-5:2016 VIRUS (protection against viruses, bacteria and fungi)
- EN 455-1/2/3/4:2000 (medical gloves for single use)
- EN1186 (food contact)




Code	Size	Pack	List Price, €	Offer Price, €
B2B9000	Small	1000	150.80	105.00
B2B9002	Medium	1000	150.80	105.00
B2B9004	Large	1000	150.80	105.00
B2B9006	X large	1000	150.80	105.00

Portwest® PW30 Safety Visitor Glasses

PORTWEST

- Moulded-in brow guard and vented side shields for excellent side protection
- Can be worn over prescription glasses
- 100% metal free
- 99% UV protection
- Anti-scratch



30% OFF

Code	List Price, €	Offer Price, €
B2B8220	5.66	4.39

Portwest® PW17 Curved Safety Glasses

- Lightweight and comfortable
- Anti-scratch coating
- Extendable side arms for secure and comfortable fit
- 99% UV protection



30% OFF

Code	List Price, €	Offer Price, €
B2B1000	5.53	3.87

SLS Lab Pro Lab Chairs

3 YEARS



- Ergonomically designed
- Height adjustable backrest and seat
- Soft and comfortable upholstery
- Made from recyclable material
- Safety tested
- Choice of castors or glides

UP TO 44% OFF



Code	Description	Material	Height, mm	List Price, €	Offer Price, €
B2B9368	Low chair on castors	Synthetic leather	440 to 620	367.90	215.00
B2B9370	High chair on glides	Synthetic leather	580 to 850	438.10	280.00
B2B9372	Standing rest chair on glides	Integral foam	510 to 780	358.80	202.00

SLS Select Low Form Beakers



- Ideal for general laboratory use
- White graduations and marking spot
- Made from high quality borosilicate glass
- High chemical and thermal resistance
- Staple item of any laboratory
- Standards equivalent to ISO 3819



Code	Capacity, mL	Dims, Ø x h, mm	Pack	List Price, €	Offer Price, €
B2B06332	25	34 x 50	12	16.90	5.59
B2B06334	50	42 x 60	12	18.20	6.11
B2B06336	100	50 x 70	12	26.00	8.26
B2B06338	150	60 x 80	12	31.20	10.47
B2B06340	250	70 x 95	12	36.40	12.16
B2B06342	400	80 x 110	12	39.00	13.65
B2B06344	600	90 x 125	6	31.20	10.34
B2B06346	1000	105 x 145	6	36.40	12.74

SLS Select Conical Flasks



- With white graduations and marking spot
- Made from high quality borosilicate glass
- High chemical and thermal resistance
- Used for many laboratory applications
- Standards equivalent to ISO 1773



Code	Capacity, mL	Dims, h x Ø x neck Ø, mm	Pack	List Price, €	Offer Price, €
B2B06358	50	80 x 54 x 24	12	45.50	15.80
B2B06360	100	105 x 64 x 29	12	49.40	17.03
B2B06362	250	145 x 85 x 31	6	33.80	11.05
B2B06364	500	184 x 103 x 36	6	40.30	11.57
B2B06366	1000	131 x 214 x 42	6	57.20	21.30

SLS Select Media Bottles



- Perfect for everyday laboratory use
- Suitable for many applications, such as storage of culture media
- Made from high quality borosilicate glass 3.3 to ISO 3585
- Heat and chemical resistance
- GL45 blue polypropylene cap and pouring ring
- White graduations and marking spot
- Sloped shoulders for easy pour
- Standards to ISO 4796-1



Code	Capacity, mL	Dims, Ø x h, mm	Pack	List Price, €	Offer Price, €
B2B06348	100	56 x 100	10	48.10	14.56
B2B06354	250	70 x 138	10	58.50	17.55
B2B06350	500	86 x 176	10	67.60	20.50
B2B06352	1000	101 x 225	10	93.60	33.20
B2B06356	2000	136 x 260	10	171.60	63.00
B2B8342	5000	186 x 330	Each	185.90	68.00
B2B8344	10000	234 x 410	Each	318.50	108.00
B2B8346	20000	299 x 505	Each	487.50	178.00


SLS Select Measuring Cylinders



- Calibrated to Class B tolerances
- Can be used for many applications where a high accuracy level of volume measurement isn't critical
- Made from high quality borosilicate glass
- High chemical and thermal resistance
- Sturdy hexagonal glass base
- White graduations
- Standards equivalent to ISO 4788



Code	Capacity, mL	Height, mm	Pack	List Price, €	Offer Price, €
B2B06368	10	135	2	11.70	3.51
B2B06370	25	160	2	13.00	3.97
B2B06372	50	195	2	14.30	4.75
B2B06374	100	250	2	18.20	5.01
B2B06376	250	300	2	29.90	9.88
B2B06378	500	350	2	44.20	14.95
B2B06380	1000	430	Each	33.80	11.12



Corning® Molecular Biology Grade Water



Code	Pack	List Price, €	Offer Price, €
B2B1252	6 x 500mL	149.50	100.00
B2B1250	6 x 1L	213.20	90.00



Corning® PBS (Phosphate Buffered Saline)

UP TO
**56%
OFF**

1x, without calcium and magnesium, pH 7.4 ±0.1.

Code	Pack	List Price, €	Offer Price, €
B2B1256	6 x 500mL	66.30	29.30
B2B1254	6 x 1L	117.00	64.00

SLS Select BenchSafe Bench Protection



Strong, tear-resistant, waterproof polyethylene surface.

UP TO
**79%
OFF**



Code	Description	Dims, w x l, mm	Pack	List Price, €	Offer Price, €
B2B06046	BenchSafe	490 x 50000	1 roll	323.70	90.00
B2B06048	BenchSafe	460 x 570	50 sheets	115.70	62.00
B2B06050	BenchSafe	600 x 490	100 sheets	267.80	90.00
B2B06052	BenchSafe Plus	600 x 490	50 sheets	276.90	59.00

Gratnells Storage Trays

5
YEARS

Gratnells
Everything in its place.

Handy trays with robust, polypropylene construction.



60%
OFF

Code	Description	Colour	Dims, l x w x h, mm	List Price, €	Offer Price, €
B2B06082	F1 shallow	Royal blue	427 x 312 x 75	16.90	6.76
B2B06084	F1 shallow	Flame red	427 x 312 x 75	16.90	6.76
B2B06086	F1 shallow	Translucent	427 x 312 x 75	16.90	6.76
B2B06090	F2 deep	Royal blue	427 x 312 x 150	28.60	11.44
B2B06092	F2 deep	Flame red	427 x 312 x 150	28.60	11.44
B2B06088	F2 deep	Translucent	427 x 312 x 150	28.60	11.44

Plastic Tray Trolleys

- Lightweight and ergonomic
- Supplied with precision bearing castors including 2 brakes
- Heavy duty construction from high quality, nylon fibre blended polymers

30%
OFF



Code	Shelves	Dims, w x d x h, mm	Platform Dims, mm	Max Load, kg	List Price, €	Offer Price, €
B2B06076	3	460 x 750 x 980	630 x 424	150	248.30	174.00
B2B06078	2	460 x 750 x 940	630 x 424	100	211.90	148.00
B2B06080	2	513 x 990 x 970	866 x 500	250	440.70	308.00

pH Buffers

Code	Description	Pack	List Price, €	Offer Price, €
B2B1294	pH 2, colourless, NIST traceable	1L	20.13	9.96
B2B1288	pH 4, red	1L	16.64	7.34
B2B1302	pH 4, red, NIST traceable	1L	12.61	5.56
B2B1300	pH 4, colourless, NIST traceable	1L	13.37	6.62
B2B1290	pH 7, yellow	1L	13.13	5.79
B2B1296	pH 7, yellow, NIST traceable	1L	12.31	5.43
B2B1304	pH 7, colourless, NIST traceable	1L	11.25	5.75
B2B1292	pH 10, blue	1L	13.69	6.04
B2B1298	pH 10, blue, NIST traceable	1L	12.31	5.43

Conductivity Standards

Code	Conductivity, µS/cm	Pack	List Price, €	Offer Price, €
B2B1310	10	500mL	27.73	14.17
B2B1312	84	500mL	27.73	14.17
B2B1308	147	500mL	27.73	14.17
B2B1306	1413	500mL	27.73	14.17
B2B1314	12880	500mL	27.73	14.17



GREAT SAVINGS!

Volumetric Solutions

Code	Description	Pack	List Price, €	Offer Price, €
B2B1328	Hydrochloric acid 0.1M (N/10)	2.5L	31.67	15.68
B2B1334	Hydrochloric acid 0.5M (N/2)	2.5L	35.37	17.51
B2B1330	Hydrochloric acid 1.0M (N/1)	1L	25.73	12.74
B2B1316	Hydrochloric acid 1.0M (N/1)	2.5L	32.07	15.87
B2B1318	Sodium hydroxide 0.111M (N/9)	5L	43.83	21.70
B2B1324	Sodium hydroxide 0.1M (N/10)	2.5L	30.77	15.23
B2B1322	Sodium hydroxide 1.0M (N/1)	2.5L	31.80	15.74
B2B1326	Sulphuric acid 0.05M (N/10)	2.5L	35.37	17.51
B2B1332	Sulphuric acid 0.5M (N/1)	2.5L	35.07	17.36
B2B1320	Sulphuric acid 2.0M (4N)	2.5L	26.13	12.94

PYREX® Volumetric Flasks, Class A

- Complies with ISO 1042 and DIN 12664
- Manufactured from chemically resistant PYREX® glass
- Polyethylene stopper



PYREX®

50% OFF

Code	Capacity, mL	Pack	List Price, €	Offer Price, €
B2B8048	20	5	84.50	42.90
B2B8052	50	5	87.10	44.20
B2B8054	100	5	107.90	55.00
B2B1352	200	5	145.60	74.00
B2B8056	250	2	59.80	29.90
B2B8058	500	2	80.60	41.60
B2B8060	1000	2	106.60	55.00

SLS Select Reagent Reservoirs



- "V" shaped well design for maximum reagent recovery
- Easy to read graduation markings located on the top edge with a fill line on inner walls
- Drip free pour-off spouts at every corner
- Manufactured in a clean room with sterile versions certified as RNase/DNase and pyrogen free
- Wide base for stability
- Tiered wall design prevents deformation when handling and reduces the chance of spills
- Nesting design allows easy separation that reduces the chance of warping or damage
- Lot numbers indicated on sterile versions
- Polystyrene

UP TO
**55%
OFF**



Code	Capacity, mL	Sterility	Inner Pack	Pack	List Price, €	Offer Price, €
B2B06039	25	Sterile	1	100	152.10	91.00
B2B06041	25	Sterile	5	200	182.00	111.00
B2B06043	25	Non sterile	Bulk	100	63.31	38.40
B2B06045	50	Sterile	1	100	198.90	94.00
B2B06047	50	Sterile	5	200	191.10	117.00
B2B06049	50	Non sterile	Bulk	100	67.60	40.40
B2B06051	100	Sterile	1	100	185.90	112.00
B2B06053	100	Sterile	5	200	218.40	131.00
B2B06055	100	Non sterile	Bulk	100	70.20	42.90

SLS Lab Basics Bottle Top Dispensers



Ergonomically designed for easy use and outstanding performance, in addition to being extremely durable and reliable. Calibrated in ISO 17025 accredited calibration facility.

- Fully autoclavable
- Easy re-calibration: a single tool to recalibrate
- Volume lock: smooth and accurate volume setting
- Universal bottle adaptor: comes with 4 additional adaptors for regular bottle sizes
- Uncomplicated mounting: snap-fit mounting of discharge tube

UP TO
**52%
OFF**



Code	Volume Range, mL	Graduations, mL	List Price, €	Offer Price, €
B2B06184	1 - 10	0.2	314.60	163.00
B2B06186	2.5 - 30	0.5	357.50	182.00
B2B06188	5 - 60	1.0	357.50	182.00
B2B9378	10 - 100	2.0	377.00	189.00

Brady® BMP51 Label Printer Kit

2 YEARS



When you need clear, durable labels on the spot, you need the BMP51 label printer. It offers portability, crisp printing, easy formatting, and convenient label sizes.

- Extensive material knowledge combined with chemical expertise enables Brady® to develop durable labels that perform throughout sample storage and processing
- Change supplies in seconds with hassle free drop-in cartridges
- Automatic label formatting
- Prints 25.40mm per second
- Use with the AC power supply, AA-batteries or rechargeable li-ion battery
- Compatible with mobile apps, built-in Bluetooth® technology provide wireless printing
- Comes with Brady WorkStation Basic Design Software Suite
- Includes hard case, rechargeable li-ion battery, USB cable, AC adaptor with power cord, product CD, Brady® printer drivers CD, quick start guide, Bluetooth® network card and MC1-1000-422 cartridge

20% OFF



Code	List Price, €	Offer Price, €
B2B1002	778.70	623.00

SLS Select Pipette Filter Tips



- Unique low binding filter tips which feature an inert, hydrophobic barrier that prevents pipette contamination
- Patented, super-micron barrier prevents pipette contamination
- Barrier will not trap liquid or contaminate samples if over-pipetting
- Reduced barrier thickness allows unrestrained air flow for exceptional accuracy and precision
- Sterile
- Free from DNase, RNase, endotoxins and pyrogens
- Long reach tips avoid the need to insert pipette cone into the sample tube, reducing contamination risk (B2B9354 + B2B9366)



UP TO 73% OFF

Code	Volume, µL	Pack	List Price, €	Offer Price, €
B2B9352	10	10 x 96	179.40	49.40
B2B9354	10	10 x 96	140.40	51.00
B2B9356	20	10 x 96	162.50	49.40
B2B9358	100	10 x 96	162.50	49.40
B2B9360	200	10 x 96	163.80	49.40
B2B9362	300	10 x 96	171.60	52.00
B2B9364	1000	10 x 100	178.10	51.00
B2B9366	1250	8 x 96	171.60	51.00

SLS Lab Pro Variable Volume Pipettes

3 YEARS

The SLS Lab Pro pipettes offer superior quality at an affordable price. These are lightweight pipettes with a handle that fits naturally in the hand. A lubricated piston assembly offers very light pipetting forces.

- Adjustable tip ejector button to adapt to both right- and left-handed users
- Clip mechanism allows easy and safe removal of tip ejector
- Fully autoclavable

UP TO
69% OFF



Code	Channel	Volume Range, µL	List Price, €	Offer Price, €
B2B06292	Single	0.2 - 2	422.50	130.00
B2B06294	Single	1 - 10	422.50	130.00
B2B06296	Single	2 - 20	422.50	130.00
B2B06298	Single	10 - 100	422.50	130.00
B2B06300	Single	20 - 200	422.50	130.00
B2B06302	Single	100 - 1000	422.50	130.00
B2B06304	Single	500 - 5000	426.40	143.00
B2B06306	Single	1000 - 10000	426.40	143.00
B2B06308	8	0.5 - 10	971.10	306.00
B2B06310	8	2 - 20	971.10	306.00
B2B06312	8	20 - 200	971.10	306.00
B2B06314	8	20 - 300	971.10	306.00
B2B06316	12	0.5 - 10	1116.70	358.00
B2B06318	12	2 - 20	1116.70	358.00
B2B06320	12	20 - 200	1116.70	358.00
B2B06322	12	20 - 300	1116.70	358.00

SLS Lab Basics Variable Volume Pipettes

3 YEARS



Single Channel:

- Ergonomic design ensuring light weight & soft plunger movement
- Click-stop system for volume selection
- Colour coded for easy identification
- Calibration conforms to EN-ISO 8655 with report enclosed with every pipette

Multi Channel:

- Smooth and light tip loading and ejection
- Leak free sealing of tips
- Manifold is easily removable, fully autoclavable and can rotate 360° for easy right or left hand operation



Code	Channel	Volume Range, µL	Compatible Tips	List Price, €	Offer Price, €
B2B06156	Single	0.1 - 2.5	10µL/10XL	188.50	60.00
B2B06158	Single	0.5 - 10	10µL/10XL	189.50	60.00
B2B06160	Single	2 - 20	10XL	193.50	60.00
B2B06162	Single	5 - 50	20µL/100µL	190.50	60.00
B2B06164	Single	10 - 100	100µL/200µL	191.50	60.00
B2B06166	Single	20 - 200	200µL/300µL	194.50	60.00
B2B06168	Single	100 - 1000	1000µL/1250µL	192.50	60.00
B2B06170	Single	500 - 5000	—	224.90	70.00
B2B06172	Single	1000 - 10000	—	224.90	70.00
B2B06174	8	0.5 - 10	10µL/10XL	841.10	241.00
B2B06176	8	5 - 50	20µL/100µL	841.10	241.00
B2B06178	8	10 - 100	100µL/200µL	841.10	241.00
B2B06180	8	20 - 200	200µL/300µL	841.10	241.00
B2B06182	8	30 - 300	200µL/300µL	841.10	241.00

Corning® Lambda™ Plus Pipette Starter Kit

All Lambda™ Plus pipettors feature smooth plunger movement and extremely low pipetting forces. Volume can be set by turning either the thumb wheel or the plunger button, and a locking mechanism prevents accidental change. Designed to maintain their calibration, even after repeated use and autoclaving. A key is included with each pipettor for easy in-house calibration.

Includes: 4 x single-channel pipettes (0.5 to 10µL, 2 to 20µL, 20 to 200µL, 100 to 1000µL), universal carousel rack for 6 single channel pipettes, 3 x Corning DeckWorks™ pipette tips (10µL, 200µL, 1000µL).



Code	List Price, €	Offer Price, €
B2B06428	1011.40	683.00

- Factory calibrated to strict ISO 8655 standards
- Fully autoclavable and UV resistant
- Designed for universal fit with all common brands of pipette tips
- Adjustable tip ejector

33% OFF



SLS Select PES Syringe Filters



The highly asymmetrical pore structure of PES membranes offers an excellent loading capacity and high flow rate for these naturally hydrophilic syringe filters. Moulded in a polypropylene shelter.

- Diameter: 25mm
- Sterile
- Recommended for preparation of protein samples, ultra-fast filtration of tissue culture media



65% OFF

Supplied in packs of 50, individually wrapped

Code	Pore Size, µm	List Price, €	Offer Price, €
B2B06412	0.22	98.80	33.80
B2B06414	0.45	98.80	33.80

Corning EcoChoice™

Supply Your Lab. Sustainably.

From Liquid Handling to Cell Culture, Corning EcoChoice products are produced, packaged, and/or distributed in an environmentally friendly manner following United States FTC Guidelines.

To learn more about the products included in the program visit www.corning.com/EcoChoice.



CORNING



Gilson MyPIPETMAN® Select Single Channel Pipettes

3 YEARS

GILSON®

Ergonomic, safe, and reliable, MyPIPETMAN® Select fully-autoclavable, air-displacement pipettes offer volume setting choice and optional handle personalisation for optimal use in various protocols.

- Simple ratchet or 3-position volume locking system including a light click and a free volume selection position
- Reduced or standard pipetting forces
- Considerably reduced or standard tip ejection forces, with a built-in ejection button integrated on top of the pipette handle
- Colours and product personalisation options



Code	Volume Range, µL	List Price, €	Offer Price, €
B2B1488	0.2 - 2	410.80	226.00
B2B1490	1 - 10	410.80	226.00
B2B1492	2 - 20	410.80	226.00
B2B1494	10 - 100	410.80	226.00
B2B1496	20 - 200	410.80	226.00
B2B1498	100 - 1000	410.80	226.00
B2B1500	500 - 5000	410.80	226.00
B2B1502	1000 - 10000	410.80	226.00

Gilson MICROMAN® E Bundles

GILSON®

An award winning design, MICROMAN® E helps you counter your common pipette problems that may affect accuracy and precision when working with problem liquids. Delivering the highest ease-of-use and control through an improved ergonomic design, a patented QuickSnap feature and a volume control button. MICROMAN® E and capillary piston tips are the strongest barrier against residual sample carryover, aerosol contamination, and cross-contamination.

- Patented QuickSnap feature automatically fixes the disposable capillary piston
- Large action button
- Volume securing button
- Comfortable finger hook



Code	Description	Volume Range, µL	Supplied with	List Price, €	Offer Price, €
B2B1504	M10E Bundle	1 - 10	MICROMAN E M10, capillary pistons CP100ST (4 cases of 960 (3840 total))	2848.30	1625.00
B2B1506	M100E Bundle	10 - 100	MICROMAN E M100, capillary pistons CP100ST (4 cases of 960 (3840 total))	2848.30	1625.00
B2B1508	M1000E Bundle	100 - 1000	MICROMAN E M1000, capillary pistons CP1000ST (20 cases of 1820 (3640 total))	2915.90	1625.00

Thermo Scientific™ Finnpiquette™ F2 Good Laboratory Pipetting (GLP) Kits

Access everything needed for pipetting in these all-inclusive kits. Thermo Scientific™ Finnpiquette™ F2 GLP (Good Laboratory Pipetting) kits provide durable, high-performance Finnpiquette™ F2 pipettes which offer maximum reliability and comfort. Built with tough PVDF components that stand up to harsh chemicals and the damaging effects of UV light, these variable volume pipettes are fully autoclavable without disassembling.

- Fully autoclavable for protection
- Tough PVDF components that stand up to harsh chemicals and the damaging effects of UV light
- Easy maintenance
- Colour coded together with Finntips™ for easier recognition of compatible tips

5
YEARS



Thermo
SCIENTIFIC



30%
OFF

Code	Kit Includes	List Price, €	Offer Price, €
B2B1134	3 x Finnpiquette™ F2 pipettes: 1 - 10µL, 10 - 100µL, 100 - 1000µL; Flex tips: 10µL, 200µL, 1mL (racks of 96); F-stand; GLP guide; reagent reservoir demo pack	1222.00	694.00
B2B1136	4 x Finnpiquette™ F2 pipettes: 0.2 - 2µL, 2 - 20µL universal, 20 - 200µL, 100 - 1000µL; Finntip™ Flex tips: 10µL, 2 x 200µL, 1mL (racks of 96); F-stand; GLP guide; reagent reservoir demo pack	1504.10	854.00
B2B1138	3 x Finnpiquette™ F2 pipettes: 10 - 100µL, 100 - 100µL, 1000 - 10000µL; Finntip™ Flex tips: 200µL, 1000µL (racks of 96), 10mL (rack of 24); F-stand; GLP guide; reagent reservoir demo pack	1246.70	709.00
B2B1140	3 x Finnpiquette™ F2 pipettes: 2 - 200µL, 20 - 200µL, 100 - 1000µL; Finntip™ Flex tips: 2 x 200µL, 1 x 1000µL (racks of 96); F-stand; GLP guide; reagent reservoir demo pack	1222.00	694.00

SLS Select Serological Pipettes



UP TO
73% OFF

- Manufactured in compliance with the current versions of the ISO 13485 and FDA CFR 21 Part 820, cGMP
- Made from USP Class VI polystyrene resin
- Crisp, dark ascending and descending as well as negative graduations
- Colour-coded rings for easy identification
- Plugged
- Non-pyrogenic
- RNase-/DNase-free
- Sterile



Code	Volume, mL	Packaging	Inner Pack	Pack	List Price, €	Offer Price, €
B2B06382	1	Individual	100	1000	396.50	116.00
B2B06384	1	Bulk	25	1000	175.50	96.00
B2B06386	2	Individual	100	1000	365.30	127.00
B2B06388	2	Bulk	25	1000	265.20	96.00
B2B06392	5	Individual	50	200	96.20	35.10
B2B06390	5	Bulk	25	500	239.20	90.00
B2B06394	10	Individual	50	200	135.20	36.40
B2B06396	10	Bulk	25	500	308.10	111.00
B2B06400	25	Individual	50	200	221.00	83.00
B2B06398	25	Bulk	20	200	360.10	133.00
B2B06402	50	Individual	20	100	287.30	103.00

SLS Lab Basics Pipette Filler

5 YEARS



Lightweight, UV resistant material, featuring adjustable valves and 3 modes (high, low, gravity). Filling and dispensing speed is easily set using the same hand by pressing the large mode button. Uses standard 0.45µm hydrophobic filters. Supplied with charger, bench stand, magnetic/fixable wall mount and 5 coloured nose cones.

48% OFF



Code	List Price, €	Offer Price, €
B2B06190	310.70	169.00

Corning® Stripettor™ Ultra Pipette Controller

2
YEARS



Light, ergonomic, motorised pipette controller for use with glass/plastic serological pipettes from 0.5 to 100mL. Conveniently positioned switches change modes and speeds quickly to handle different liquid volumes and viscosities. Fully charged, the batteries enable up to 8 hours of continuous use. The large LCD display clearly indicates battery status, pipetting mode, and speed. Supplied with universal charging adapter, 2 x 0.2µm filter, 3 x coloured nose-pieces, wall-mounted holder, and charging stand.



55%
OFF

Code	List Price, €	Offer Price, €
B2B06430	421.20	190.00

National Diagnostics ProtoGel


Forms an electrophoresis matrix that is ideal for the separation of proteins and polypeptides. Stabilised, ready-to-use acrylamide/methylene bisacrylamide solution (37.5:1 ratio). Aldehyde and acrylic acid free.

25%
OFF

Supplied in 1L bottles

Code	Description	List Price, €	Offer Price, €
B2B1274	ProtoGel 30%	204.10	155.00
B2B1276	ProtoGel 40%	243.10	183.00

national
diagnostics



National Diagnostics SequaGel UreaGel Denaturing Gel System

national
diagnostics

The UreaGel System consists of UreaGel concentrate, UreaGel diluent, and UreaGel buffer. Prepares any commonly used gel formulation up to 20% monomer (19:1 acrylamide: bisacrylamide).

25%
OFF



Code	Pack	List Price, €	Offer Price, €
B2B1282	19:1 system 1L kit	191.10	143.00

National Diagnostics AccuGel

national
diagnostics

Stabilised, ready-to-use solution of 40% (w/v) acrylamide to bisacrylamide for consistently crystal clear gels. Aldehyde and acrylic acid free.

25%
OFF

Supplied in 1L bottles



Code	Description	List Price, €	Offer Price, €
B2B1278	AccuGel 19:1 (40%)	178.10	135.00
B2B1280	AccuGel 29:1 (40%)	182.00	138.00

Corning® LSE Mini Microcentrifuge

2 YEARS



A compact, lightweight and easy-to-use centrifuge. It includes an 8-place rotor that will accept standard 1.5 to 2.0mL microcentrifuge tubes with adapters for 0.5/0.4mL and 0.2mL tubes, and a 4 place rotor for PCR strip tubes.

35% OFF

- Close the lid to start, press the lid release button to stop
- Quick release rotor system eliminates the need for tools to exchange rotors
- Electronic braking provides rapid deceleration for more efficient sample prep
- Compact, rugged design withstands heavy use in crowded lab environment
- Dual lid switch provides safe operation
- Ergonomic design allows for comfortable handling



Code	Max Speed, RPM	Max RCF, x g	Dims, w x d x h, mm	List Price, €	Offer Price, €
B2B7112	6000	2000	148 x 174 x 122	282.10	183.00

SLS Lab Basics Mini Centrifuge

2 YEARS



Ideal for microfiltration and quick spin downs from the walls and caps of microcentrifuge tubes. The compact design saves bench space and features an easy-open clear lid. Simply close the lid for acceleration and open the lid for deceleration, or alternatively use the on/off switch to control.

62% OFF

- Easy-to-use with dual start/stop function
- Compact design
- Whisper quiet operation
- Ideal for quick spin downs of microtubes and PCR tubes
- Universal voltage
- Rotor change without tools
- Accelerates and brakes in seconds
- Supplied with 8 place 1.5/2.0mL microtube rotor and 16 place (2 x 8 strips) PCR rotor



Code	Max Speed, RPM	Max RCF, x g	Dims, w x d x h, mm	List Price, €	Offer Price, €
B2B06202	7000	2680	160 x 170 x 122	275.60	104.00

SLS Lab Basics my-FUGE 12 Place Centrifuge

2 YEARS



55% OFF

Eliminate the need to change rotors when switching between microtubes and PCR strips with the unique COMBI-Rotor™ (included) allowing the running of 12 x 1.5/2.0mL microtubes and 4 PCR strips simultaneously. With a fixed speed that produces 2000 x g, this centrifuge is perfect for quick spin downs.

- Twice the capacity of most mini centrifuges
- Near silent operation
- Starts and stops with closing/opening of the lid
- Conserves valuable bench space



Code	Max Speed, RPM	Max RCF, x g	Dims, w x d x h, mm	List Price, €	Offer Price, €
B2B7092	5500	2000	146 x 203 x 108	798.00	371.00

SLS Lab Basics 12 Place Microcentrifuge

2 YEARS



64% OFF

Compact and powerful high-speed centrifuge, ideal for research applications including sedimentation of cells and viruses and isolation of macromolecules such as DNA, RNA, proteins or lipids. It consists of a large LCD display which provides all visual information and a unique cooling design which minimises rotor heating.

- Whisper quiet operation - less than 49dB
- Automatic door lock
- Automatic internal diagnosis
- Polypropylene rotor is fully autoclavable
- Run time: 30 sec - 99 min
- Pulse operation for quick spins
- Sound-alert function
- Over-temperature and over-speed detector
- Supplied with 12 position 1.5/2.0mL microtube rotor



Code	Max Speed, RPM	Max RCF, x g	Dims, w x d x h, mm	List Price, €	Offer Price, €
B2B06204	15000	15100	245 x 255 x 140	1953.90	702.00

OHAUS Frontier™ 5707 Multi Centrifuge

2 YEARS



A reliable, compact, low speed general purpose centrifuge. Designed with convenient operation in mind, and featuring an intuitive interface. The compact profile helps to save valuable bench space in labs.

30% OFF

- Convenient control on an intuitive interface, which allows for responsive operation - even when wearing gloves
- Brushless quiet motor
- Small footprint
- Speed range: 200 to 6800rpm
- Maximum RCF: 4445 x g
- Dims, w x d x h: 277 x 356 x 236mm



Code	Supplied with	List Price, €	Offer Price, €
B2B1044	Angle rotor for 8 x 15mL round bottom tubes	1591.20	1128.00
B2B1046	Angle rotor for 4 x 15/50mL round/conical bottom tubes	1523.60	1066.00

SLS Flowgen Plate Spinner

2 YEARS



Rapidly spin down droplets in PCR or microplates to improve PCR yields or give more consistent assay results. The swing out rotor has two plate carriers that rest at a 75° angle. This allows plates to be inserted confidently without sealing tapes or caps. Most samples can be spun down in less than 20 seconds. To end a run, simply open the lid and the automatic, electric brake brings the rotor to a quick, smooth stop in just 4 seconds.

- Unique swing-out rotor design prevents spillage
- Accepts most types of PCR plates
- Capacity: 2 x PCR plates (when stacking skirted PCR plates, max. capacity is 4 plates); 2 x microplates
- Remarkably small footprint

58% OFF



Code	Max Speed, RPM	Max Speed, x g	Dims, w x d x h, mm	List Price, €	Offer Price, €
B2B06236	2550	600	230 x 260 x 197	1241.50	644.00

SLS Flowgen 2D BenchRocker

2 YEARS



Designed to provide the precise speeds and tilt angles required for a broad range of molecular and biological mixing applications. The user can adjust both parameters to match the vessel size and the volume of liquid being mixed, yielding optimum results. Provides a gentle wave effect for non-foaming mixing, as is required for most blot washing and gel work. When set to higher speeds and more extreme tilt angles, they produce aggressive agitation for vigorous sample mixing.

47% OFF

- Accepts stackable platforms (clearance = 70mm)
- Adjustable speed and tilt for a wide range of applications
- Dual platform accessory doubles work surface
- Cold room and incubator safe



Code	Speed Range, RPM	Tilt Angle, °	Platform Dims, mm	Dims, w x d x h, mm	List Price, €	Offer Price, €
B2B7080	2 - 30	0 - 30	350 x 300	350 x 300 x 200	1245.40	722.00

SLS Flowgen 3D MiniMixer

2 YEARS



Multi-functional shaker which provides a 3-dimensional “nutating” motion for thorough, foam-free mixing in blood and centrifuge tubes, as well as in a variety of flat vessels. Feature maintenance free, brushless motors capable of loads up to 2kg and are safe for use in cold rooms and incubators.

51% OFF

- Includes dimpled mat; ideal for mixing in blood & centrifuge tubes
- Optional flat mats are also available for mixing other vessel types
- Stacking platforms sold separately, effectively doubling the usable surface area
- Tri-directional motion for thorough, uniform mixing



Code	Speed, RPM	Tilt Angle, °	Platform Dims, mm	Dims, w x d x h, mm	List Price, €	Offer Price, €
B2B7082	24 (fixed)	20	270 x 190	270 x 190 x 200	681.20	371.00

IKA Lab Dancer Vortex Mixer

2 YEARS

IKA®

The IKA Lab Dancer is a compact test tube shaker with a touch function, designed for mixing small sample tubes up to 30mm diameter.

- Fixed speed (2800 RPM)
- Includes light 12V power pack set
- Upper casing and the test tube surface are made from inert plastic, bottom section is a coated, zinc die-casting
- Protection class IP40

55% OFF



Code	List Price, €	Offer Price, €
B2B9140	520.00	234.00

SLS Lab Basics Vortex Mixer

2 YEARS

SLS LAB BASICS



Compact and stable design with electronic speed control ensures the same speed is maintained at all times, even during changes of load and also features continuous or touch operation. The orbital diameter of 4mm provides effective and efficient mixing inside the sample.

- Quiet and compact stable design
- Continuous or touch operation
- Electronic speed control for constant speed even during changes in load
- Aluminium cast base with silicone feet for excellent stability and vibration damping

67% OFF



Code	Speed Range, RPM	Dims, w x d x h, mm	Weight, kg	List Price, €	Offer Price, €
B2B06222	0 - 2500	127 x 160 x 130	3.5	388.70	130.00

SLS Lab Basics DigiRoll 6 Tube Roller


2 YEARS



6 tube roller providing a rocking and rolling motion for optimum mixing of viscous samples. Equipped with a powerful brushless DC motor for maintenance free long life and quiet operation. Microprocessor controller gives accurate speed under variable load, and the programming feature means the user can save and run up to 9 user defined programs.

- Digital display with soft touch keypad
- IP 21 protection class
- Timer from 1 min to 99 min and infinite mode
- User can set pulse time from 30 to 99 seconds
- Adjustable rollers spacing to hold different diameter tubes
- Stackable design with robust construction

50% OFF



Code	Capacity	Speed Range, RPM	Tilt Angle, °	Dims, w x d x h, mm	List Price, €	Offer Price, €
B2B06224	15 x 3/4mL tubes	10 - 80	±3	502 x 301 x 93	729.30	390.00

SLS Lab Basics 10 Roller Tube Roller

2 YEARS



Designed for gentle, thorough mixing. As the roller mechanism rotates through each complete revolution, the right side of each roller is gently elevated about 13mm and returns to the horizontal starting position. This additional, gentle up/down motion provides a “wave” effect and guarantees that the entire sample is subjected to complete, thorough mixing, end to end. This built in tilt feature provides a level of homogeneous mixing uniformity that cannot be matched by any stationary roller apparatus.

- Gentle rolling motion
- Smooth ±5° tilt action
- For tubes/bottles from 8 to 200mm diameter

63% OFF



Code	Speed Range, RPM	Dims, w x d x h, mm	List Price, €	Offer Price, €
B2B9036	38	450 x 180 x 90	1375.40	845.00

Benchmark Roto-Mini™ Plus Rotator

2 YEARS

Benchmark Scientific

Benchmark's new Roto-Mini™ series of rotating mixers provide a wide range of mixing capabilities. Suitable for an array of laboratory applications including resuspension, protein binding, nucleic acid purification, etc. the mixers include interchangeable tube holders for accommodating all common tube sizes from 0.5mL to 50mL. The motion can be adjusted from vertical (end over end) mixing, to horizontal (rolling or hybridisation style) mixing.

- Includes tube holders for common tube sizes, 11 x 1.5/0.2mL (pack of 2), 5 x 10-15mL (pack of 2), 5 x 5-7mL (pack of 2), 6 x 50mL (pack of 1)
- "Mix" function: Rotating in combination w/ oscillations (increased mixing)
- "Pause" function: Rotating with intermittent "stops" during rotation
- "Rock" function: Back and forth, gentle rocking motion (see-saw)
- Additional rocking platform (4.5 x 3in), as well as a 96 x 0.2mL tube/strip/plate holder for mixing PCR vessels in the "Mix" (oscillating) mode

50% OFF



Code	Speed Range, RPM	List Price, €	Offer Price, €
B2B9016	5 to 70	743.60	380.00

SLS Lab Basics Digital Orbital Shaker

5 YEARS

LAB BASICS



A dependable and versatile shaker for a vast range of protocols. Create your own matrix for vessels of all shapes and sizes with hi-lo platform and bungee cords. Instantly adjusts to weight load changes and unbalanced loads with no-stop electronic motor feedback allowing for truly reproducible results.

- Durable ABS construction suitable for use in incubators (excluding CO₂) and cold rooms within 2 to 40°C; 20 to 80% RH, non-condensing
- Run time: 0 to 74 hours and 59 minutes, 1 second increments or continuous
- Soft start and shut down feature reduces spilling from full vessels
- Designed to handle heavy loads up to 4.5kg
- Overload protection shut-off prevents overloading
- Supplied with skid-free rubber platform mat, 8 x bungee cords, universal hi-lo platform with soft rubber edge bumpers, power adapter (110-240VAC, 50/60 Hz) with 4 interchangeable plug types

30% OFF



Code	Orbit, mm	Speed Range, RPM	Platform Dims, mm	Dims, l x w x h, mm	List Price, €	Offer Price, €
B2B7300	19	20 - 300	279 x 279	314 x 197 x 314	1203.80	845.00

SLS Lab Pro Hydron Benchtop pH Meter

3 YEARS



A reliable and economical benchtop meter for routine measurements of pH, mV and temperature. Featuring five-point calibration with auto-buffer recognition, automatic temperature compensation (ATC) and datalogging capabilities for the storage and recall of up to 100 data sets, the Hydron is well suited to routine applications across academic laboratories, industrial settings and education. A compact footprint, large easy-to-read display and splash-proof keyboard also make it user-friendly and space saving for the busy workspace.

- Measures pH, mV, relative mV, and temperature
- Automatic temperature compensation (ATC)
Requires optional temperature probe (not supplied)
- Non-skid pads hold meter steady during operation
- Large dual LCD display
- Integral electrode holder
- Hold function and stability indicator
- Supplied with pH electrode and arm



Code	Dims, w x d x h, mm	List Price, €	Offer Price, €
B2B9376	155 x 175 x 69	739.70	449.00

Mettler Toledo FiveEasy™ Benchtop pH/mV Meters

1 YEAR



Ideally suited for applications in the laboratory, the FiveEasy™ and FiveEasy™ Plus benchtop instruments provide high quality pH/mV measurements with the simple click of a button. Compact in design, and featuring various data export opportunities, the FiveEasy™ series instruments are the perfect companion to get reliable measurement data, all at a reasonable price.

- Large, well-structured display with intuitive button arrangement and simple menu
- Compact design saves space
- FiveEasy™ Plus meters allow data to be exported either directly to a printer or a PC
- Electrode arm sold separately



These items may incur an additional delivery charge

Code	Description	List Price, €	Offer Price, €
B2B9180	FiveEasy F20 pH/mV meter only	565.50	408.00
B2B7234	FiveEasy F20 pH/mV standard kit with LE438 sensor	715.00	546.00
B2B9182	FiveEasy Plus FP20 pH/mV meter only	800.80	579.00
B2B7236	FiveEasy Plus FP20 pH/mV meter standard kit with LE438 sensor	910.00	692.00
B2B7238	FiveEasy Plus FP20 pH/mV meter bio kit with LE410 sensor	999.70	719.00
B2B7240	FiveEasy Plus FP20 pH/mV micro kit with LE422 sensor	997.10	724.00
B2B7242	FiveEasy Plus FP20 pH/mV Tris kit with LE420 sensor	978.90	706.00

Jenway 550 Handheld pH and Temperature Meter

2 YEARS

Jenway®

Model 550 is a general purpose portable pH meter offering 2 point pH calibration and automatic buffer recognition. This model simultaneously displays both the temperature compensated pH readings and temperature. This small, lightweight meter has an LCD display encompassed in a splash proof housing.

- Automatic calibration
- Manual or Automatic Temperature Compensation (ATC)
- Auto shut off 10 minutes
- 5000 hours battery life
- Supplied with electrode, probe, buffers and carry case



25% OFF

Code	Range, pH	Resolution, pH	List Price, €	Offer Price, €
B2B9346	0 to 14	0.01	327.60	246.00

SLS Lab Basics Hotplate Stirrer, 280°C

LAB BASICS



Stainless steel stirrer with a ceramic coated hotplate which resists corrosion. Features a digital control system, ideal for use in physics, chemistry and biotech labs.

- Heating temperature up to 280°C
- LED display shows temperature and speed
- 50°C HOT warning indicates residual hotplate temperature
- ABS chemical resistant casing
- Includes **FREE** external temperature sensor PT1000 and support clamp

57% OFF



Code	Stirring Capacity, L	Speed Range, RPM	Max Temp, °C	Plate Ø, mm	List Price, €	Offer Price, €
B2B06238	3	100 - 1500	280	135	595.40	254.00

SLS Lab Basics Hotplate Stirrer, 340°C



Stirrer hotplate with ceramic coated stainless steel plate, widely used in chemical synthesis, physical and chemical analysis, bio-tech labs.

- Simple running interface easy to use and program, automatically identifies temperature sensor PT1000 and transfers to PT1000 operation mode
- LCD display shows target and actual temperatures, as well as set and actual speed
- Brushless DC motor - maintenance free and explosion-proof
- Fully closed assembly guarantees safety and long service life, effectively prevents the liquid damage
- HOT warning indicates residual hotplate temperature
- Includes **FREE** external temperature sensor PT1000 and support clamp

60% OFF



Code	Stirring Capacity, L	Speed Range, RPM	Max Temp, °C	Plate Ø, mm	List Price, €	Offer Price, €
B2B06240	20	100 - 1500	340	135	1037.40	416.00

IKA RCT Basic Ready-To-Go Solution



The RCT basic ready-to-go solution includes all components required for precise temperature control of your sample with the RCT basic magnetic stirrer.

- Tempered shatterproof glass surface for optimal chemical resistance and easy cleaning
- Largest display in its class with easy-to-read LED display
- Includes a stand rod together with an extension arm and a boss head clamp. They ensure the correct and safe positioning of the PT 1000 temperature sensor, which is also included in the delivery
- Also includes a universal silicone cover for beakers with 600 and 1000mL capacity. The chemically highly resistant cover fulfils three functions at once: it is a splash guard, minimises energy requirements when used as a lid, and reduces the noise that can occur when air is drawn in during rapid stirring

25% OFF



Code	Stirring Capacity, L	Speed Range, RPM	Temp Range, °C	Dims, w x d x h, mm	List Price, €	Offer Price, €
B2B1166	20	50 to 1500	Ambient to 310	160 x 270 x 85	1302.60	978.00

Grant QBD2 Block Heater

3
YEARS

GRANT



A versatile general purpose system with removable/interchangeable blocks and a comprehensive specification to suit most dry block heating applications. Range of convenient features includes alarms, single and dual point calibration, programmed start/stop, and 'offset' for known sample temperature variation.

- Digital temperature control for optimal precision
- Includes block removal tool for easy and safe removal of blocks
- Stability/uniformity: $\pm 0.1^{\circ}\text{C}$ @ 37°C

15%
OFF

FREE
BLOCK
SPECIFY WHEN
ORDERING!

Code	Temp Range, °C	No. Block Positions	Dims, w x d x h, mm	List Price, €	Offer Price, €
B2B06434	Ambient +5 to 130	2	200 x 285 x 120	1034.80	924.00

Heater Blocks

Choose 1 of the below blocks for **FREE** when you buy a QBD2 block heater.

Code	Alt Ref	Description
B2B06438	QB-10	24 x 10mm test tubes, hole depth 50mm
B2B06440	QB-12	24 x 12mm test tubes, hole depth 50mm
B2B06442	QB-13	12 x 13mm test tubes, hole depth 50mm
B2B06444	QB-16	12 x 16mm test tubes, hole depth 50mm
B2B06446	QB-18	12 x 18mm test tubes, hole depth 50mm
B2B06448	QB-24	5 x 24mm test tubes & universal bottles, hole depth 50mm
B2B06450	QB-H	56 x 0.2mL microtubes, $\varnothing 6.5\text{mm}$, hole depth 14mm
B2B06452	QB-E0	24 x 0.5mL microtubes, $\varnothing 8\text{mm}$, 30mm hole depth
B2B06454	QB-E1	24 x 1.5mL microtubes, $\varnothing 10.8\text{mm}$, hole depth 35mm
B2B06456	QB-E2	24 x 2mL microtubes, $\varnothing 11\text{mm}$, 35mm hole depth
B2B06458	QB-50	4 x 50mL tubes, $\varnothing 29\text{mm}$, hole depth 50mm



SLS Flowgen Digital Dry Baths

2 YEARS



Digital dry baths with accurate “set and walk away” digital temperature selection, eliminating the need for external thermometers and repetitive “fine tuning” of a temperature control knob. Simply enter the desired temperature on the digital touchpad and the dry bath provides accurate temperature with real time monitoring that continuously maintains the selected temperature.

- Assorted blocks for a wide variety of tube sizes sold separately - see SLS website for full list of accessories
- Include an easy to use block lifter with a temperature insulated handle
- Built-in user re-calibration function, to guarantee long term temperature accuracy
- Temperature range: ambient +5 to 150°C
- Temperature accuracy: $\pm 0.2^{\circ}\text{C}$, increments: 0.1°C , uniformity: $\pm 0.2^{\circ}\text{C}$
- Digital timer is built into the touchpad display (1 to 999 minutes)

55% OFF



Code	No. Block Positions	Dims, w x d x h, mm	List Price, €	Offer Price, €
B2B7088	1	200 x 230 x 80	809.90	423.00
B2B7090	2	220 x 260 x 80	1011.40	553.00

SLS Lab Pro BeadBug Microtube Homogeniser

2 YEARS



High energy benchtop homogenisers that sets the performance standard for personal sized cell disruption and lysis instruments. The optimised mixing motion causes rapid cell disruption through constant high velocity impact from the hardened micro-beads chosen specifically for your sample type. Developed for samples too tough to be homogenised in a common lab vortexer, the BeadBug™ provides a convenient and economical alternative to the traditional, high capacity homogenisers on the market today.

UP TO 51% OFF

- Extremely powerful mixing for lysis, grinding or homogenisation
- Faster and more effective than tissue grinders
- Homogenise up to 6 samples in disposable 2mL screw cap microtubes
- Extremely compact
- Eliminates the cross contamination



Code	Capacity	Speed Range, RPM	Dims, w x d x h, mm	List Price, €	Offer Price, €
B2B7094	3 x 2mL	2800 to 4000	170 x 210 x 135	1569.10	774.00
B2B1486	6 x 2mL	2500 to 4350	220 x 355 x 205	3633.50	2461.00

SLS Lab Pro Safevac Aspiration System

2 YEARS



- Designed for laboratory waste recovery and separation of liquid and solid
- Vacuum power can be set to different levels to achieve 1 - 15mL/s aspirating speed
- Sensitive level sensor to prevent liquid overflow during operation
- Waste bottle, tubing and handle are fully autoclavable
- Wide range of adapters to fit tubes and microplates

61% OFF



Code	Vacuum Range, mbar	Vacuum Speed, mL/S	Volume, L	Dims, w x d x h, mm	List Price, €	Offer Price, €
B2B06242	0 - 600	1 - 15	4	180 x 240 x 450	2160.60	845.00

Corning® Transwell®-Clear Inserts



Permeable supports, also known as cell culture inserts, are an essential tool for the study of both anchorage-dependent and independent cell lines.

- Produce a cell culture environment that closely resembles an in vivo state
- Allow polarised cells to carry out metabolic activities in a more natural manner because the cells feed both apically and basolaterally
- Co-culture cells with or without cell-to-cell contact
- Treated for optimal cell attachment
- Excellent visibility under phase contrast microscopy
- Supplied in multiple well plates
- Sterile



UP TO 41% OFF

Code	Membrane Ø, mm	Membrane	Pore Size, µm	Pack	List Price, €	Offer Price, €
B2B1198	6.5	Polyester	0.4	48	483.60	283.00
B2B1200	6.5	Polycarbonate	0.4	48	510.90	294.00
B2B1202	6.5	Polyester	3.0	48	483.60	321.00
B2B1204	12	Polyester	3.0	48	483.60	321.00
B2B1206	24	Polycarbonate	3.0	24	308.10	231.00
B2B1208	24	Polyester	3.0	24	283.40	220.00
B2B1210	24	Polycarbonate	8.0	24	293.80	220.00
B2B1212	75	Polycarbonate	3.0	24	835.90	567.00

SLS Lab Basics Inverso TC100 Inverted Microscopes

1
YEAR



Ideal for the typical working laboratory and is built to a high-quality specification. It is robust enough to withstand the rigours of constant daily use and with a quintuple position nose-piece fitted as standard, it is ideally suited for multiple observation techniques and/or magnifications.

- Trinocular head inclined at 45°
- Eyepieces: 10/20mm wide field
- Objectives: 4X, 40X plan-achromatic LWD/10X, 20X, 40X phase contrast
- Condenser: NA 0.3 (removable), working distance 72mm
- Stage: 160 x 250mm with additional mechanical stage (2 interchangeable stage plates) stage extending board
- Focusing: coaxial coarse and fine
- Illumination: 3W LED
- Epi fluorescence module adds blue excitation (460 - 490nm) and green excitation (480 - 550nm)

UP TO
47%
OFF



Code	Description	List Price, €	Offer Price, €
B2B06416	With mechanical stage LED	5010.20	2730.00
B2B06418	With epi fluorescence module	15151.50	9100.00


SLS Lab Basics Tablet Microscope Camera



Tablet camera designed for microscopy applications with a high-definition 9.7" colour LCD touchscreen. Equipped with software that allows the user to preview an image, set the white balance, capture images and videos as well as having measurement and annotation capabilities.

- Crystal display, RK3066 dual-core 1.5Hz CPU
- Touch-screen operation, can be used as a small computer
- Includes Wi-Fi and Bluetooth wireless networking for easy file, HDMI output
- Not suitable for fluorescence work
- **FREE** C-mount adapter when purchased with B2B06416 microscope

53% OFF



Code	Camera	List Price, €	Offer Price, €
B2B06420	15fps at 1024 x 768; 1/2.5 [4:3] 5mpx CMOS	1957.80	943.00



SLS Select Lens Cleaning Tissue

Ideal solution for cleaning lenses and other optical surfaces made from glass, quartz or plastic.

Supplied in packs of 50

Code	Dims, mm	Offer Price, €
B2B06248	80 x 100	7.80

SLS Lab Pro Analogue Ultrasonic Baths

3 YEARS



With capacities from 1.5L to 25L, the SLS Lab Pro analogue ultrasonic baths offer simple analogue timer and temperature controls, providing entry level ultrasonic baths ideal for cleaning small items for use in a wide range of applications. Supplied with a stainless steel basket and plastic lid. B2B8280 has a non-adjustable heater element.

UP TO 30% OFF

- Ambient to 70°C temperature control on heated models
- 0 – 15 minute timer
- Compact and user friendly



Code	Capacity, L	Heated	Overall Dims, w x d x h, mm	Int Dims, w x d x h, mm	List Price, €	Offer Price, €
B2B8278	1.5	No	180 x 160 x 190	150 x 140 x 100	447.20	332.00
B2B8280	1.5	Yes	180 x 160 x 190	150 x 140 x 100	552.60	403.00
B2B8282	2.5	No	270 x 170 x 210	240 x 140 x 100	572.00	442.00
B2B8284	2.5	Yes	270 x 170 x 210	240 x 140 x 100	661.70	488.00
B2B8286	4.5	Yes	330 x 180 x 275	300 x 150 x 150	1175.20	962.00
B2B8288	13	Yes	375 x 345 x 275	330 x 300 x 150	1487.20	1229.00
B2B8290	25	Yes	550 x 345 x 365	500 x 300 x 200	2003.30	1554.00

Benchmark BioClave™ Mini Research Autoclave

2 YEARS

Benchmark Scientific

Despite the space-saving exterior dimensions, the stainless steel chambers are surprisingly large, accommodating a variety of liquids, media, instruments, glassware, plasticware and other common research laboratory items. Benchtop models include a mechanical and electrical safety interlock that prevents the door from being opened until the pressure has reached zero PSI. With a large digital display and fully automatic operation, all segments of the cycle (fill, sterilise, exhaust and dry) commence and run to completion by simply pressing the start button. An optional thermal mini-printer is also available for providing a record of sterilisation parameters and a USB drive can be used to record settings and transfer them to a PC.

45% OFF

- Fully automatic, just press start
- Adjustable sterilisation times
- Extremely compact
- Built in water tank, does not require connection to an external water supply



Code	Capacity, L	Dims, w x d x h, mm	List Price, €	Offer Price, €
B2B9026	8	510 x 340 x 330	6918.60	3920.00

SLS Lab Basics Compact Precision Balances

5 YEARS

LAB BASICS



- Accurate, high quality, attractive, and stackable units
- Perfect for applications where portability or easy storage are paramount
- External calibration
- Supports multiple weighing units like counting, % weighing
- Hygienic and rustproof stainless steel pan
- Security slot at the back for wire-locking to prevent theft
- Power supply: AC adaptor or 4 AA size dry batteries (batteries not included)

UP TO 53% OFF



Code	Capacity, g	Readability, g	List Price, €	Offer Price, €
B2B06024	310	0.01	414.70	237.00
B2B06026	3100	0.1	484.90	237.00

SLS Lab Pro P-Series Precision Balances

5 YEARS



- One touch automatic calibration
- Compact, B5 size footprint
- Fast, 1 second stabilisation
- Large bright vacuum fluorescent display
- Shock absorber function
- Multiple weighing units
- GLP/GMP/GCP/ISO compliant
- Statistical calculation function
- ACAI – Automatic Counting Accuracy Improvement
- Dims, w x d x h: 193 x 262.5 x 85.5mm

UP TO
58% OFF



Code	Capacity, g	Readability, g	Plate Ø, mm	List Price, €	Offer Price, €
B2B06114	122	0.001	130	1081.60	621.00
B2B06116	220	0.001	130	1199.90	662.00
B2B06254	320	0.001	130	1506.70	662.00
B2B06118	520	0.001	130	1705.60	918.00
B2B06120	1220	0.01	150	1081.60	621.00
B2B06122	2200	0.01	150	1158.30	662.00
B2B06256	3200	0.01	150	1506.70	662.00
B2B06290	5200	0.01	150	1612.00	918.00

SLS Lab Pro A-Series Analytical Balances

5 YEARS



- Compact footprint
- Breeze break with rotary doors that slide behind the balance and can be removed with one touch
- Ideal for applications where space is at a premium
- Reverse backlit LCD display for easy to read weighing results
- Statistical calculation function eliminates the need for a stats printer
- Standard RS-232C
- Fast, compact SHS sensor, response time ~2 seconds

UP TO
54% OFF



Code	Capacity, g	Readability, mg	Calibration	List Price, €	Offer Price, €
B2B06106	102	0.1	External	1362.40	757.00
B2B06250	102	0.1	Internal	1748.50	939.00
B2B06108	152	0.1	External	1666.60	844.00
B2B06110	152	0.1	Internal	2046.20	978.00
B2B06112	252	0.1	External	1899.30	978.00
B2B06252	252	0.1	Internal	2341.30	1180.00

OHAUS PR Series Balances

2
YEARS

Offering accuracy and repeatability in essential weighing applications in laboratory, industrial and education settings, PR Series analytical and precision balances deliver competitive performance at an economical price. Featuring RS232 connectivity for easy communication, and a backlit display and a simple interface for uncomplicated operation, the PR is perfectly designed for your workplace.


- Equipped with 3 essential weighing modes
- RS-232 connectivity for data transfer and storage
- Easy-to-read, bright backlit display and a simple user interface, making it easy to operate
- Small footprint saves desktop space while providing a large weighing surface
- Durably constructed, and features a stainless steel pan to withstand day-to-day use



Code	Capacity, g	Readability, mg	Pan Dims, mm	Calibration	List Price, €	Offer Price, €
B2B1004	120	0.1	Ø 90	External	1279.20	884.00
B2B1006	120	0.1	Ø 90	Internal	1397.50	1023.00
B2B1008	220	0.1	Ø 90	External	1405.30	962.00
B2B1010	220	0.1	Ø 90	Internal	1508.00	1101.00
B2B1012	220	1	Ø 120	External	949.00	633.00
B2B1014	220	1	Ø 120	Internal	1127.10	771.00
B2B1016	420	1	Ø 120	External	946.40	646.00
B2B1018	420	1	Ø 120	Internal	1079.00	788.00
B2B1020	520	1	Ø 120	External	1021.80	681.00
B2B1022	520	1	Ø 120	Internal	1210.30	828.00
B2B1024	1600	10	Ø 180	External	946.40	646.00
B2B1026	1600	10	Ø 180	Internal	1155.70	793.00
B2B1028	2200	10	Ø 180	External	965.90	668.00
B2B1030	2200	10	Ø 180	Internal	1188.20	819.00
B2B1032	4200	10	Ø 180	External	955.50	699.00
B2B1034	4200	10	Ø 180	Internal	1157.00	846.00
B2B1036	4200	100	Ø 180	External	863.20	593.00
B2B1038	4200	100	Ø 180	Internal	1079.00	740.00
B2B1040	6200	100	Ø 180	External	904.80	619.00
B2B1042	6200	100	Ø 180	Internal	1106.30	757.00



Laboratory Equipment



Do more with OHAUS

From stirrers to shakers, centrifuges to dry block heaters, lifts to clamps, the OHAUS portfolio is filled with products perfect for life science applications, giving you countless opportunities to maximize your reach in your customer's laboratories.

Don't limit yourself to just measurement – **Do More!**

Ingeniously Practical

SLS Flowgen Incu-Shaker™ Incubated Shaker

2
YEARS




Compact shaking incubator with a remarkably small footprint. Accepts several platforms and a variety of flasks, tubes and other common vessels.

The standard platform (included) features a non-slip, rubber coated surface, ideal for tissue culture flasks, Petri dishes and staining trays.

**59%
OFF**

- Extremely compact, just 280mm wide
- Touch screen control over time, speed and temperature
- Horizontally circular 19mm orbit for aeration & mixing
- Instantly exchange flask clamps with MAGIC Clamp™ accessories
- Program STEP feature for linking consecutive programs



Code	Temp Range, °C	Speed Range, RPM	Orbit, mm	Dims, w x d x h, mm	List Price, €	Offer Price, €
B2B7084	Ambient +5 - 70	30 - 300	19	280 x 480 x 330	5746.00	2730.00

JULABO SW22 SW Shaking Water Bath




JULABO shaking water baths provide numerous state-of-the-art features for common day-to-day laboratory tasks.

- Sloped edges keep water in the stainless steel bath tank even when bath lid is open
- Splash-proof design
- Warning and cut-off protection for high/low temperature
- Convenient bath drains
- Bright LED display
- Reliable microprocessor PID temperature control
- Removable shaking carriage
- Dry-running protection with audible and optical alarm
- Removable platform for full immersion of the sample containers

Package includes universal basic tray for assembling Erlenmeyer flasks from 25 to 1000mL, including spring clamps

**25%
OFF**



Code	Speed Range, RPM	Temp Range, °C	Temp Stability, °C	Dims, w x d x h, mm	List Price, €	Offer Price, €
B2B1048	20 to 200	+20 to 99.9	±0.2	700 x 350 x 260	4997.20	3748.00

Lift-Up Makrolon Cover

Code	List Price, €	Offer Price, €
B2B1050	373.10	329.00

SLS Lab Pro Shaking Water Bath

3 YEARS



Shaking water bath, featuring precision PID temperature control with an option to enable a run back timer. The controls allow observation of set and actual temperature simultaneously. A broad range of accessory flask clips and racks ensures flexibility for routine and specialised work.

The heating footprint provides rapid energy transfer, resulting in quicker heat up times and a reduction in energy consumption and improved temperature uniformity.



14% OFF



- Painted surfaces feature anti-bacterial finish
- Bold LED display of measured temperatures in real-time and in increments of $\pm 0.1^{\circ}\text{C}$, using a precision PID temperature controller
- Easy to use controls, utilising touch keypads for setting temperature and time value
- Temperature alarms to protect your work
- Shaking speed control is by analogue dial
- Stroke length is variable up to 40mm
- Shaking system is quiet in use
- Supplied with polycarbonate lid

Code	Capacity, L	Temp Range, $^{\circ}\text{C}$	Shaking Speed, RPM	Dims, w x d x h, mm	List Price, €	Offer Price, €
B2B9374	28	Ambient +5 to 100	0 to 200	715 x 332 x 290	2587.00	2308.00

Meridian Bioscience ISOLATE II Kits

meridian BIOSCIENCE[®]
LIFE. SPECIALLY. LIFE. APPROVED.

15% OFF

Supplied in kits of 50 preps

Code	Description	List Price, €	Offer Price, €
B2B1258	ISOLATE II plasmid mini kit	150.80	134.00
B2B1260	ISOLATE II PCR and gel kit	180.70	160.00
B2B1262	ISOLATE II genomic DNA kit	275.60	244.00
B2B1264	ISOLATE II plant DNA kit	347.10	307.00
B2B1266	ISOLATE II RNA mini kit	453.70	402.00

Grant ecocool Recirculating Baths

3 YEARS

GRANT



25% OFF

Innovative, eco-friendly, refrigerated heated circulating baths offering significant running cost savings whilst delivering powerful cooling. Consisting of two models, the ecocool range is supplied assembled as ready to use kits, complete with accessory hosing, clips and connectors as standard.

- Active cooling through the whole temperature range
- True energy saving of up to 80% against standard compressor units
- Thermostat and chiller work in harmony, neither will operate alone, eliminating any danger of overheating or freezing
- Single front switch for user convenience



These items may incur an additional delivery charge

Code	Alt Ref	Temp Range, °C	Dims, w x d x h, mm	List Price, €	Offer Price, €
B2B9106	ecocool 100R	-20 to 100	245 x 430 x 640	4864.60	3649.00
B2B9108	ecocool 150R	-30 to 150	240 x 550 x 640	5617.30	4213.00

SLS Lab Pro S500 Mini Recirculating Chiller

2 YEARS

LAB PRO

34% OFF

With a sophisticated touchscreen controller and 500W cooling power the S500 Mini is ideal for many laboratory applications. Built to save space, the Mini is about the size of the average desktop PC.

- A touchscreen interface
- Universal 90-260 VAC input voltage and 50/60Hz input frequency suitable for use all over the world
- Variable speed compressor and fan
- Whisper quiet
- Continual adjustment of refrigerant mass flow rate to control duty
- Water system constructed from 12mm push fit fittings
- USB port for downloading system data



Code	Temp Range, °C	Cooling Capacity, kW	Flow Rate, L/min	List Price, €	Offer Price, €
B2B06404	-10 to +60	0.5	3.5	7702.50	5070.00

SLS Lab Pro Water Baths

4 YEARS

Digital water baths providing a stable temperature environment with digital PID temperature control for precision with an LED display. Controls feature auto alarm settings, illuminated on/off switch, heater and over temperature indications.

- Temperature range: ambient +5 to 99°C
- Over temperature alarm with heater cut off
- Touch pad controls with easy wipe surface
- Painted surfaces feature antibacterial protection, immersed components are corrosion resistant
- Free additional year warranty (4 years total)



UP TO
37% OFF



Unstirred

- Sensitivity: $\pm 0.2^{\circ}\text{C}$, uniformity: $\pm 0.1^{\circ}\text{C}$
- Supplied with clear, polycarbonate lid

Code	Capacity, L	Ext Dims, w x d x h, mm	Int Dims, w x d x h, mm	Drain Outlet	List Price, €	Offer Price, €
B2B7076	2	332 x 185 x 135	300 x 150 x 65	No	683.80	614.00
B2B06266	4	332 x 185 x 290	300 x 150 x 150	No	741.00	579.00
B2B06268	14	361 x 332 x 290	325 x 300 x 150	No	997.10	631.00
B2B06270	22	538 x 322 x 290	500 x 300 x 150	Yes	1029.60	767.00
B2B7078	28	538 x 332 x 290	500 x 300 x 200	Yes	1190.80	858.00

UP TO
37% OFF



Stirred

- Sensitivity: $\pm 0.05^{\circ}\text{C}$, uniformity: $\pm 0.01^{\circ}\text{C}$
- Robust thermostirrer constructed from stainless steel for durability
- Low water level is indicated and heating is automatically suspended with an automatic restart when the bath is filled
- Can be set for water temperature or a combination of temperature and time
- Timer programmable to commence once a preset temperature is reached and setting retained once unit is turned off

Code	Capacity, L	Ext Dims, w x d x h, mm	Int Dims, w x d x h, mm	List Price €	Offer Price, €
B2B06272	8	271 x 332 x 170	129 x 300 x 150	1293.50	1076.00
B2B06274	14	361 x 332 x 170	219 x 298 x 150	1307.80	1088.00
B2B06276	22	537 x 332 x 170	395 x 298 x 150	1378.00	1147.00

SLS Lab Pro Type 2 and 3 Water Purification Systems

1 YEAR

SLS Lab Pro water purification system available in two water quality versions:

Type 3 – Primary grade water (reverse osmosis) suitable for glass washers, autoclave feed, stability chambers and steam/humidity generators.

Type 2 – General laboratory grade water (deionisation) for buffer, reagent and media preparation, sample dilution, general chemistry and teaching applications.

- Low cost, one box solution
- Wall or bench mounted
- 50% recovery rate keeps water costs to a minimum
- Energy consumption <60W
- Unique disposable RO maintains peak efficiency
- Consumables changed in seconds
- Built-in 35L reservoir
- Minimal water wastage
- Mercury free UV

UP TO
44%
OFF

INSTALLATION
SERVICE
AVAILABLE
- PLEASE
ENQUIRE



Code	Model	Make Up Rate, L/hr	List Price, €	Offer Price, €
B2B7316	Choice 10 type 2 (DI)	10	6661.20	3894.00
B2B7074	Choice 10 type 2 (DI) UV	10	7124.00	4160.00
B2B7072	Choice 10 type 3 (RO)	10	5753.80	3315.00
B2B7314	Choice 10 type 3 (RO) UV	10	6571.50	3705.00
B2B06262	Choice 20 type 2 (DI)	20	6700.20	4160.00
B2B06264	Choice 20 type 2 (DI) UV	20	7898.80	4453.00
B2B06258	Choice 20 type 3 (RO)	20	6542.90	3894.00
B2B06260	Choice 20 type 3 (RO) UV	20	7124.00	4160.00

SLS Lab Pro Insulated Eco Drying Cabinets

2 YEARS



SLS Lab Pro eco drying cabinets are designed with energy efficiency in mind, utilising thermal insulation and a user programmable digital control, for drying laboratory glassware, surgical instruments or media.

- Energy saving thermal insulation to 5 sides
- Low power consumption
- Easy accessible control system
- Digital temperature controller
- Digital 7 day 24hr timer
- Economical to run / lower running costs
- Dual circulating fans and easy roll mounting wheels on floor standing units
- Corrosion free stainless steel internal chamber
- Anti-microbial powder coat paint to external surfaces
- Temperature range of 30 to 80°C

These items may incur an additional delivery charge



UP TO
42%
OFF

Code	Type	Capacity, L	Airflow	Door Style	Dims, w x d x h, mm	Energy Consumption, kWh/24hr*	List Price, €	Offer Price, €
B2B06326	Bench	113	Static	Sliding	765 x 450 x 732	6.840	2893.80	2470.00
B2B06324	Bench	227	Static	Sliding	1000 x 550 x 807	7.968	3044.60	2795.00
B2B06328	Floor standing	426	Fan-assisted	Hinged	635 x 650 x 1870	13.920	7382.70	4342.00
B2B06330	Floor Standing	885	Fan-assisted	Hinged	1168 x 650 x 1870	18.960	9750.00	5850.00

*at 70°C setpoint

SLS Lab Basics Mini Vacuum Pumps

1 YEAR



UP TO
36% OFF

Single-head, dry-running devices used in a wide range of laboratory applications. They transfer, compress and pump down without contamination.

- 100% oil-free transfer
- PTFE coated version for slightly aggressive or corrosive gases and vapours
- Maintenance-free
- High level of gas tightness
- IP20 motor protection
- Silencer fitted to outlet port
- 6mm hosetail on inlet



Code	Diaphragm Material	Delivery, L/min	Ultimate Vacuum, mbar	List Price, €	Offer Price, €
B2B06244	EPOM rubber	6	100	452.40	325.00
B2B06246	PTFE coated	5.5	160	533.00	364.00

Welch MPC 090 E Chemical Duty Diaphragm Pump



Specifically designed using Welch's well proven diaphragm technology which ensures ultra quiet operation and long service life. The standard equipment of a high accuracy regulator allows for soft start filtration, to prevent damage to the filter membrane, whilst allowing a powerful final vacuum level to be achieving for fast results. A built in catch pot prevents accidental ingestion of liquid into the pump.

40% OFF

- Complete solution for vacuum filtration
- Manual vacuum regulator with dial gauge and liquid trap
- Sturdy housing design
- Super quiet running, low vibration
- Ultra portable and requires minimal bench space due to small footprint
- Controllable filtration power
- Oil-free
- Vacuum display and adjustment for soft start
- Includes chemical duty diaphragm pump, housing in casing with vacuum gauge, regulator and liquid trap, AC/DC power adapter



Code	Pumping Speed, L/min	Ultimate Pressure, mbar	Dims, w x d x h, mm	List Price, €	Offer Price, €
B2B1336	13	100	144 x 198 x 244	1249.30	794.00

Haier Biomedical Laboratory Fridges and Freezers

2 YEARS

Haier Biomedical
Intelligent Protection of Life Science



UP TO
54% OFF

Reliable, energy-efficient and environmentally friendly refrigeration. Featuring microprocessor controller, LED display with battery backup, alarm functions and locks as standard.

- Efficient low noise hydrocarbon (HC) compressor, with low power consumption
- Completely green refrigeration solution
- High density foam insulation for rigidity and stable storage temperature within 3°C
- Secure and safe, suitable for multiple users
- Microprocessor electronic temperature controller
- LCD digital temperature display
- Multiple alarms including high and low temperature, sensor error, power failure, door ajar, high ambient and remote alarm



These items may incur an additional delivery charge

Code	Capacity, L	Temp Range, °C	Dims, w x d x h, mm	Sparkfree	List Price, €	Offer Price, €
B2B9126	118	+3 to +16	597 x 635 x 835	Yes	2294.50	1196.00
B2B7292	310	+3 to +16	605 x 598 x 1840	No	2646.80	1437.00
B2B9128	310	+3 to +16	605 x 598 x 1840	Yes	3448.90	1596.00
B2B7298	92	-10 to -25	640 x 610 x 810	No	1502.80	1035.00
B2B9124	92	-10 to -26	640 x 610 x 810	Yes	2031.90	1115.00
B2B7296	262	-10 to -25	700 x 705 x 1665	No	2992.60	1758.00

Corning® CoolCell® Containers

CORNING

Corning® CoolCell®, in combination with a -80°C freezer, will provide alcohol-free freezing at the rate of -1°C/minute that is ideal for cryopreservation of most cells and cell lines. Using a combination of uniform-density cross-linked polyethylene foam, a solid state core, and radial vial symmetry, freezing profiles are consistent and reproducible. The foam is non-absorbent and will impose negligible change in the freezer environment; thereby protecting nearby frozen samples. The removal of vials is accomplished by tipping the device upside down so the vials slide out.

- Easy to use
- Alcohol and fluid-free freezing
- Lower cost of use than alcohol-based devices
- High cell recovery and cell viability
- Reproducible
- Simple, consistent way to standardise controlled-rate freezing

14% OFF



Code	Capacity	Colour	List Price, €	Offer Price, €
B2B1214	12 x 1/2mL cryovials	Purple	237.90	204.00
B2B1216	12 x 1/2mL cryovials	Green	237.90	204.00
B2B1218	12 x 1/2mL cryovials	Orange	237.90	204.00
B2B1220	12 x 1/2mL cryovials	Pink	237.90	204.00
B2B1222	30 x 1/2mL cryovials	Purple	650.00	558.00

SLS Lab Pro Statebourne Biorack Storage Refrigerators

5 YEARS

The Biorack series of refrigerators provide highly efficient storage of bulk quantities of cryovials. Racking systems housed within these ultra low loss cryogenic refrigerators enable users to store large quantities of biomedical material over long periods of time, safe in the knowledge that storage temperatures even in the vapour phase, will be below -190°C.

- Advanced super insulation and ultra high vacuum techniques allow storage times between refills of up to 6 months
- Supplied complete with racks and polycarbonate cryoboxes
- Ultra-low evaporative losses
- Compatible with all major cryobox brands
- Heavy duty lockable enclosure offers excellent security
- Liquid or vapour phase option available
- Temperature data logging device available
- Storage of 96 well plates, straws, 5mL tubes, blood bags, canes and cord blood bags

These items may incur an additional delivery charge

SUPPLIED WITH
FREE ROLLER
BASE WORTH
€888!

25%
OFF



In partnership with
STATEBOURNE
cryogenics



Code	Model	Supplied with	List Price, €	Offer Price, €
B2B8360	Biorack 750	5 x racks, 30 x 5 x 5 cryoboxes	4305.60	3391.00
B2B8362	Biorack 3000	6 x racks, 30 x 10 x 10 cryoboxes	6546.80	5156.00
B2B8364	Biorack 4800	6 x racks, 48 x 10 x 10 cryoboxes	8191.30	6452.00
B2B8366	Biorack 6000	6 x racks, 60 x 10 x 10 cryoboxes	8794.50	6926.00

Azenta Semi-Automated Sheet Heat Sealer



A semi-automatic heat sealer which is compatible with a wide range of seals and plates of differing designs and heights. With variable temperature and time settings, sealing conditions are easily optimised to produce a 100% seal, eliminating sample loss. The sealing process is controlled by an electric mechanism; this unique feature eliminates operator variation, giving a consistent seal every time and reducing the damage caused to microplates by over-sealing.

- Suitable for a wide range of plate types
- Rapid heating element to allow for a quick start up within minutes
- Real time temperature display to allow monitoring of heating process
- Included standard plate carrier (59-2001) for sealing deep well plates and most skirted plates (other adapters sold separately)

Code	Dims, w x d x h, mm	List Price, €	Offer Price, €
B2B1524	181 x 275 x 310	5291.00	3333.00



Heat Sheet Seals

Supplied in packs of 100

Code	Description	List Price, €	Offer Price, €
B2B1526	Individual Access Peel Heat Seal, peelable heat sealing foil, 12 strips, each covering 8 wells, sheet format (127 x 100mm)	291.85	204.00
B2B1528	DMSO Resistant Peel Heat Seal, solvent resistant heat sealing foil, 1 perforated roll (125 x 78mm)	157.30	85.00
B2B1530	Universal Peel Heat Seal, peelable heat sealing foil with wide material compatibility (125 x 78mm)	104.00	72.00
B2B1532	Clear Weld Heat Seal, optically clear heat sealing film (125 x 78mm)	150.80	81.00
B2B1534	Thermal Bond Heat Seal, heavy duty heat sealing foil (125 x 78mm)	139.10	88.00
B2B1536	Peel Heat Seal, peelable heat sealing foil (125 x 78mm)	118.30	75.00
B2B1538	Pierce Heat Seal, pierceable heat sealing foil (125 x 78mm)	126.10	75.00
B2B1540	Individual Access Pierce Heat Seal, pierceable heat sealing foil, 96 individual seals in sheet format (127 x 100mm)	291.85	234.00
B2B1542	Pierce Heat Seal Strong, strong heat sealing foil (125 x 78mm)	135.20	86.00
B2B1544	Individual Access Pierce Heat Seal Strong, strong heat sealing foil, 96 individual seals in sheet format (127 x 100mm)	323.70	238.00
B2B1546	Foil Heat Seal, aluminium heat sealing foil (125 x 78mm)	126.10	64.00
B2B1548	Polystyrene Foil Heat Seal, peelable heat sealing foil (125 x 78mm)	118.30	64.00
B2B1550	Gas Permeable Heat Seal, heat sealing membrane (125 x 78mm)	118.30	64.00
B2B1552	Clear Heat Seal, gas permeable, clear heat sealing film, with 3mm slits for gas transfer (125 x 78mm)	146.90	92.00

BACK 2 BASICS | 2024

GREAT
OFFERS
INSIDE

- England & Wales: +44 (0)115 982 1111
- Scotland: +44 (0)123 643 1857
- Northern Ireland: +44 (0)28 9262 1100
- Republic of Ireland: +353 (0)1 4069 464
- International: +44 (0)115 977 5060
- East Africa: +254 (0)728 156294



www.scientificlabs.ie

EXCLUSIVE
offers on essentials for your laboratory

eppendorf



PYREX®

Benchmark
Scientific

PORTWEST

Haier Biomedical
Intelligent Protection of Life Science

SG FLOWGEN



AZENTA
LIFE SCIENCES

Julabo



G GRANT

STATEBOURNE
cryogenics

IKA®



SG LAB
BASICS



GILSON®