



## **VORTEX 3**

Vortex shaker suitable for short-time operation (touch function), activated by pressing shaker attachment or continuous operation.

- Wide speed range, infinitely adjustable

- Different applications thanks to 3 interchangeable attachments and 7 inserts (e.g. Eppendorf tubes, microtiter plates, Erlenmeyer flasks 250 ml etc.), please order separately

- Attachments securely click onto appliance in any position
- Special strap (VG 3.36, page 51) ensures easy handling of round/Erlenmeyer flasks
- Sturdy metal zinc die cast casing
- Compact design
- Short-time operation activated by pressing attachment (touch function)
- Stable at high speeds thanks to special feet (silicon base with ultra high vibration damping)
- Eccentric with ball bearings
- Suitable for continuous operation with low self heating thanks to self ventilation of motor

Shaking movement: orbital Orbital diameter: 4 mm Infinitely adjustable speed range: 500 - 2.500 rpm

Accessories: VG 3.1 Standard attachment, VG 3.36 Erlenmeyer flask attachment (for VG 3.3), VG 3.2 One-hand attachment, VG 3.3 Universal attachment, VG 3.31 Test tube attachment (for VG 3.3), VG 3.32 Test tube attachment (for VG 3.3), VG 3.33 Test tube attachment (for VG 3.3), VG 3.34 Test tube attachment (for VG 3.3), VG 3.35 Test tube attachment (for VG 3.3), VG 3.37 Microtiter plate attachment (for VG 3.3)

| Technical Data                             |                       |
|--|-----------------------|
| Type of movement                           | orbital               |
| Shaker diameter [mm]                       | 4                     |
| Motor rating input [W]                     | 58                    |
| Motor rating output [W]                    | 10                    |
| Permissible ON time [%]                    | 100                   |
| Speed min (adjustable) [rpm]               | 500                   |
| Speed range [rpm]                          | 0 - 2500              |
| Speed display                              | none                  |
| Timer                                      | no                    |
| Operating mode                             | continuous operation  |
| Touch function                             | yes                   |
| Shaking table lock                         | no                    |
| Working with microtiter plates             | yes                   |
| Number of microtiter plates                | 1                     |
| Dimensions (W x H x D) [mm]                | 127 x 136 x 149       |
| Weight [kg]                                | 4.5                   |
| Permissible ambient temperature [°C]       | 5 - 40                |
| Permissible relative humidity [%]          | 80                    |
| Protection class according to DIN EN 60529 | IP 21                 |
| RS 232 interface                           | no                    |
| Analog output                              | no                    |
| Voltage [V]                                | 200 - 240 / 115 / 100 |
| Frequency [Hz]                             | 50/60                 |
| Power input [W]                            | 60                    |
| Ident. No.                                 | 0003340000            |