

265

Nitrate TT

**Chromotropic Acid** 

1 - 30 mg/l N

## Instrument specific information

The test can be performed on the following devices. In addition, the required cuvette and the absorption range of the photometer are indicated.

Instrument Type	Cuvette	λ	Measuring Range
MD 600, MD 610, MD 640, MultiDirect	ø 16 mm	430 nm	1 - 30 mg/l N
SpectroDirect, XD 7000, XD 7500	ø 16 mm	410 nm	1 - 30 mg/l N

#### **Material**

Required material (partly optional):

Reagents	Packaging Unit	Part Number	
VARIO Nitra X Reagent, Set	1 Set	535580	
The following accessories are required.			

Accessory	Packaging Unit	Part Number
Plastic funnel with handle (white)	1 pc.	471007

# **Application List**

- · Waste Water Treatment
- · Drinking Water Treatment
- · Raw Water Treatment

### **Notes**


1. A small amount of solid material remains may be undissolved.

## Implementation of the provision Nitrate with Vario Vial Test

Select the method on the device



Open digestion vial (Reagent A) .



Put 1 ml sample in the vial. Carefully invert several




times to mix the contents.

Note: Will get hot!



Close vial(s).



Place sample vial in the sample chamber. • Pay attention to the positioning.



Press the **ZERO** button.




ple chamber.




Remove vial from the sam- Add Vario Nitrate Chromo- Close vial(s). tropic powder pack.





Invert several times to mix the contents (10 x).



Place **sample vial** in the sample chamber. • Pay attention to the positioning.



Press the **TEST** (XD: **START**) button.



Wait for 5 minute(s) reaction time.

Once the reaction period is finished, the measurement takes place automatically.

The result in mg/l Nitrate appears on the display.

### **Analyses**

The following table identifies the output values can be converted into other citation forms.

Unit	Cite form	Scale Factor
mg/l	N	1
mg/l	NO <sub>3</sub>	4.43

### **Chemical Method**

Chromotropic Acid

## **Appendix**

#### **Bibliography**

P. W. West, G. L. Lyles, A new method for the determination of nitrates, Analytica Chimica Acta, 23, 1960, p. 227-232

a) determination of free, combined and total | b) Reactor is necessary for COD (150 °C), TOC (120 °C) and total -chromium, - phosphate, -nitrogen, (100 °C) | a) MultiDirect: Adapter is necessary for Vacu-vials® (Order code 19 20 75) | b) Spectroquant® is a Merck KGaA Trademark | b) alternative reagent, used instead of DPD No.1/No.3 in case of turbidity in the water sample caused by high concentration of calcium and/or high conductivity | b) additionally required for determination of bromine, chlorine dioxide and ozone in the presence of chlorine | b) Reagent recovers most insoluble iron oxides without digestion | b) additionally required for samples with hardness values above 300 mg/l CaCO<sub>3</sub> | b) high range by dilution | f including stirring rod, 10 cm