



# TurboCycler 3

## High-Throughput Triple-Block Gradient PCR Thermal Cycler



### **Triple-Block Flexibility**

Three distinct PCR protocols can be run at the same time, perfect for multi-user environments and diverse experiments with low samples.




### **High-Throughput Efficiency**

Maximize throughput with up to 3 x 48 x 0.1/0.2 ml samples.



### **Fast Gradient Optimization**

PCR conditions across the three independent blocks are easily adjusted and range from 30 to 100 °C with a maximum span of 30 °C.



### **Advanced Ramp Rate Control**

Ramp rate can be adjusted from 0.1 to 5.0 °C/sec, to accommodate different assays including CRISPR-related experiments.



### **Intuitive Operation**

Effortless programming on a large 10.1" color touch screen with a user-friendly interface.



### **Continuous Reliability: Zero Downtime**

Each of the three independent block modules can be independently calibrated to ensure uninterrupted operation during maintenance.

# Specifications

## Sample Block

3 x 48 Well, Gradient Block	Compatible with 0.2 ml or 0.1 ml PCR tube, strip, non-skirted, and semi-skirted 48-well plate
-----------------------------	---

## Block Temperature

Block Temperature Range	4.0 - 100 °C
Max. Heating / Cooling Rate	5.0 °C/sec / 3.0 °C/sec
Temperature Accuracy	+/- 0.3 °C
Temperature Uniformity	+/- 0.4 °C
Adjustable Ramp Rate	Yes, 0.1 - 5.0 °C/sec

## Gradient Temperature

Gradient Direction	Vertical across the block
Gradient Temperature Range	30 - 100 °C
Gradient Temperature Difference	Max. span 30 °C

## Heated Lid

Temperature Setting Range	35 - 120 °C or off
Temperature Accuracy	+/- 1.0 °C

## Software

Portability of Protocols	Save and transfer to another TurboCycler via USB flash drive
Stored Program No.	> 4000 sets
Registered User Folder No.	100 sets
User Folder Password Protection	Yes
Run Status Report	Yes, HTML output and transfer via USB flash drive
Real-Time Temp. Profile Export	Yes, CSV output and transfer via USB flash drive
Tools	Tm calculator, Copy number convertor, Master mix preparation wizard

## General

Display	10.1" color LCD with capacitive touch panel
Data Port	1 USB A front port for USB flash drive
Auto restart after Power Outage	Yes
Footprint Dimensions (H x W x D)	236 mm x 356 mm x 362 mm
Weight	13 kg
Power Supply	AC 100 - 240 V, 50/60 Hz, 1000 W
Certification	CE

Specifications are subject to change without prior notice.

## Ordering Information

TCTT-4810 Gradient TurboCycler 3 with Three Independent Blocks

TCTT-a001 Tube Frame

TCTT-a002 5 mm Compression Mat x 10 pcs



ISO 13485

Authorized Distributor