

thermo scientific



# Thermo Scientific GENESYS Vis and UV-Vis Spectrophotometers

Legendary reliability. Unrivaled usability.

**ThermoFisher**  
SCIENTIFIC

# GENESYS—developed for users, designed for results

Built on the foundation of 60 years of spectroscopy experience, the next generation Thermo Scientific™ GENESYS™ family of Vis/UV-Vis spectrophotometers provides exceptional performance with a contemporary design.

- Start taking measurements immediately with the simple-to-use, high-resolution, color-display start menu
- Exchange samples with ease with large, accessible sample compartment
- Save your data fast any way you want it with multiple data-export options

There is a GENESYS spectrophotometer you can count on to provide accurate, reproducible results for your application requirements.



Outstanding features to help you meet your teaching, quality

For teaching labs, research labs and industrial QC requiring robust construction, ease-of-use and software capability.



GENESYS 30 Visible Spectrophotometer

### Modern power meets traditional simplicity

- The gold standard in basic spectrophotometers
- Large sample compartment supports the use of cuvettes and test tubes
- Removable, washable compartment liner for easy clean-up
- Ideal solution when OD600 is your primary need



GENESYS 40 Vis/50 UV-Vis Spectrophotometers

### Advanced usability, modern functionality

- 7-inch, high-resolution touchscreen interface
- Local control increases speed and reliability for routine analysis
- Large sample compartment with front access simplifies sample handling
- Wi-Fi ready—save data and methods, print results from on-board control

## Choose the instrument that's right for you

Instrument	Spectral region	Optics	Display
GENESYS 30	Vis	Single Beam	5-inch color screen
GENESYS 40	Vis	Dual Beam	7-inch touchscreen
GENESYS 50	UV-Vis	Dual Beam	7-inch touchscreen, tiltable
GENESYS 140	Vis	Dual Beam	7-inch touchscreen, tiltable
GENESYS 150	UV-Vis	Dual Beam	7-inch touchscreen, tiltable
BioMate 160	UV-Vis	Dual Beam	7-inch touchscreen, tiltable
GENESYS 180	UV-Vis	Double Beam	7-inch touchscreen, tiltable

\*8-cell changer comes standard with the GENESYS 180

\*\*Three-year warranty available upon instrument registration





# GENESYS instrument specifications

Description	GENESYS 30	GENESYS 40	GENESYS 140	GENESYS 50	GENESYS 150	BioMate 160	GENESYS 180
<b>Optical Design</b>	Single Beam				Dual Beam		Double Beam
<b>Spectral Bandwidth</b>	5 nm			2 nm			
<b>Light source (Typical Lifetime)</b>	Tungsten-Halogen (>1000 hours)			Xenon Flash Lamp (>5 years typical, 3 years guaranteed)			
<b>Detector</b>	Silicon Photodiode	Dual Silicon Photodiodes					
<b>Wavelength</b>	<b>Range</b>	325–1100 nm			190–1100 nm		
	<b>Accuracy</b>	±2 nm				±0.5 nm	
	<b>Repeatability</b>	<±1 nm				<±0.2 nm	
	<b>Scan Speed</b>	Automatic—up to 1200 nm/min	Automatic—up to 1800 nm/min		Slow, medium and fast (up to 1600 nm/min)		
	<b>Data Resolution</b>	1 nm	0.2 nm, 0.5 nm, 1 nm, 2 nm, 5 nm				0.1 nm, 0.2 nm, 0.5 nm, 1 nm, 2 nm, 5 nm
<b>Photometric</b>	<b>Range</b>	–3A to +3A	–3A to +3.5A		–2A to +3.5A		
	<b>Display</b>	–3A to +3A, 0 to 200 000 %T, 0 to 9 999 999 C				–3A to +5A	
	<b>Accuracy</b>	±0.002A (0–0.3A) 0.5% of ABS reading (0.301A – 2.5A)				±0.002A at 0.5A ±0.004A at 1.0A ±0.008A at 2.0A	
	<b>Repeatability<sup>1</sup></b>	±0.002 A				±0.001A at 1A	
	<b>Noise<sup>2</sup></b>	≤0.001A at 0A ≤0.001A at 1A ≤0.002A at 2A				≤0.00020A at 0A at 260 and 500 nm ≤0.00030A at 1A at 260 and 500 nm ≤0.00040A at 2A at 260 and 500 nm	
	<b>Drift<sup>3</sup></b>	<0.002A/Hr	<0.0010A/Hr		<0.0005A/Hr		
<b>Stray Light</b>	<0.1%T at 340 nm and 400 nm	<0.05%T at 340 nm and 400 nm		< 1.0%T 198 nm (KCl), <0.05%T at 220 nm (NaI), <0.03%T at 340 nm (NaNO <sub>2</sub> )			
<b>Baseline Flatness</b>	<0.003A	±0.005A			±0.002A		
<b>Display</b>	5-inch diagonal, 32-bit color display, 800 × 480 pixels	7-inch color touchscreen, fixed, high definition, 800 × 1280 pixels	7-inch color touchscreen, tiltable, high definition, 800 × 1280 pixels	7-inch color touchscreen, fixed, high definition, 800 × 1280 pixels	7-inch color touchscreen, tiltable, high definition, 800 × 1280 pixels		
<b>Keypad</b>	Tactile rubber 23 keys with numeric keypad	Touchscreen					
<b>Sample Compartment</b>	<ul style="list-style-type: none"> <li>• Accessible from top, front or side</li> <li>• All platforms can accommodate 100 mm cells</li> <li>• Available accessory for test-tubes up to 25 mm diameter and 150 mm height</li> <li>• Removable, washable sample compartment liner with magnetic placement and hold-down</li> </ul>	<ul style="list-style-type: none"> <li>• Accommodates (optional):</li> <li>• 8-position cell changer</li> <li>• 4-position cell changer (long path cells)</li> <li>• Peltier thermostatted cell holder (20–60 °C)</li> <li>• Sipper accessory</li> </ul>	<ul style="list-style-type: none"> <li>• Accessible from top, front or side</li> <li>• Able to accommodate cells up to 100 mm pathlength</li> <li>• Available accessory for test-tubes up to 25 mm diameter and 150 mm height</li> <li>• Removable, washable sample compartment liner with magnetic placement and hold-down</li> </ul>	<ul style="list-style-type: none"> <li>• Accommodates (optional):</li> <li>• 8-position cell changer</li> <li>• 4-position cell changer (long path cells)</li> <li>• Peltier thermostatted cell holder (20–60 °C)</li> <li>• Sipper accessory</li> <li>• Fiber optic probe coupler</li> </ul>	<ul style="list-style-type: none"> <li>• 8-position cell changer (standard)</li> <li>• Also accommodates (optional):</li> <li>• 4-position cell changer (long path cells)</li> <li>• Peltier thermostatted cell holder (20–60 °C)</li> <li>• Sipper accessory</li> <li>• Fiber optic probe coupler</li> </ul>		
<b>Printer</b>	Snap-on printer available						
<b>Connectivity</b>	<ul style="list-style-type: none"> <li>• USB-A on front face supports flash memory devices for method and data storage</li> <li>• USB-B on side supports connection to a Windows computer running optional remote control software; export data to PC via USB</li> </ul>	<ul style="list-style-type: none"> <li>• Single USB-A supports flash memory devices for method and data storage</li> <li>• Duplex USB-A supports connection to a Windows computer running optional remote control software, keyboard, mouse</li> <li>• Export data to network or PC via Ethernet or Wi-Fi</li> <li>• Print via USB, Ethernet or Wi-Fi</li> </ul>					
<b>Languages</b>	English (Available soon: Spanish, German, French, Italian, Portuguese, Russian, Chinese, Japanese, Korean, Thai)						
<b>Dimensions</b>	35.5 × 38.5 × 19.5 cm (L × W × H)						
<b>Weight</b>	7.5 kg						
<b>Power Requirements</b>	External AC to DC converter. Voltage and Frequency (Hz) selected automatically, 100–240 volts, 50–60 Hz.						
<b>Warranty</b>	2 years standard with 1 year extension upon registration of the instrument with Thermo Fisher Scientific within 6 months of purchase						

1. Measured at 1.0A at 546 nm 2. RMS at 500 nm. 60 consecutive measurements. 3. At 500 nm after warmup. 2hrs GENESYS 30, 1hr all others. \*\*\* Visit [www.thermofisher.com/connect](http://www.thermofisher.com/connect) for details

Find out more at [thermofisher.com/genesys](http://thermofisher.com/genesys)

**ThermoFisher**  
SCIENTIFIC

© 2018 Thermo Fisher Scientific Inc. All rights reserved. Microsoft and Windows are registered trademarks of Microsoft Corporation. All other trademarks are the property of Thermo Fisher Scientific and its subsidiaries. Specifications, terms and pricing are subject to change. Not all products are available in all countries. Please consult your local sales representative for details. **BR52989\_E 03/18M**