Scientific Laboratory Supplies - Safety Data Sheet

(in accordance with regulation (EU) 2015/830 and regulation (EC) 1272/2008)

Revision: 1.1 Revision date: 16 April 2021 Date printed: 17 August 2022

CHE1120

Section 1. Identification

1.1 Product Identifier CHE1120

Product Name 1-AMINOBUTANE pure 250ml.

CAS Number 109-73-9

REACH Registration No 01-2119470233-46-XXXX

Molecular Formula

CH, (CH,), NH, =73.14

1.2 Relevent identified uses of the substance or mixure & uses advised against

Uses of Material Chemical for industrial and laboratory use. Not suitable for domestic use.

1.3 Supplier Scientific Laboratory Supplies

SCIENTIFIC LABORATORY SUPPLIES

Wilford Industrial Estate

Ruddington Lane

Wilford Nottingham NG11 7EP

UNITED KINGDOM

Phone 0115 9821111 Fax 0115 9825275

Email sales@scientific-labs.com

1.4 Emergency Telephone (08:00-17:00) 0115 9821111

(24hr) 112 (Have this document to hand)

Section 2. Hazards Identification

2.1 Classification of the substance or mixture

Classification according to regulation 1272/2008/EC

Flammable liquid, category 2 H225: Highly flammable liquid and vapour.

Skin corrosion/irritation, category 1A H314: Causes severe skin burns and eye damage.

Acute toxicity, category 4 (oral)

Acute toxicity, category 4 (dermal)

H302: Harmful if swallowed.

H312: Harmful in contact with skin.

Acute toxicity, category 4 (inhalation) H332: Harmful if inhaled.

Spec target organ tox - single, category 3 H335: May cause respiratory irritation.

2.2 Label elements

Labelling according to regulation 1272/2008/EC

Signal word Danger

Hazard Pictograms







Highly flammable liquid and vapour. Harmful if inhaled. Harmful in contact with skin. Harmful if swallowed. Hazard Statements

Causes severe skin burns and eye damage. May cause respiratory irritation.

Keep away from heat / sparks/open flames/hot surfaces - No smoking. Wear protective gloves / protective Precautionary Statements

clothing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do and continue rinsing. IF ON SKIN: Wash with plenty of soap and water.

Section 3. Composition

3.1 Substances

Component	CAS No.	EEC No.	REACH No.	Conc w/w	CLP Classification (1272/2008/CE)
Butylamine	109-73-9	203-699-2	01-2119470233-46-XXXX	>98%	Flam. Liq. 2,Skin Corr. 1A,Acute Tox. 4 (O),Acute Tox. 4 (D),Acute Tox. 4 (I),STOT SE 3 (I)

Section 4. First Aid

4.1 Description of first aid measures

Irrigate thoroughly with plenty of water for at least 10 minutes, holding the eye open. OBTAIN MEDICAL Eves

ATTENTION.

Wash off skin thoroughly with water. Remove contaminated clothing immediately and wash before re-use. In Skin

severe cases or if exposure has been great, OBTAIN MEDICAL ATTENTION.

Inhalation Remove from exposure. Keep warm and at rest. If there is difficulty in breathing give oxygen if available. If

breathing stops or shows signs of failing, apply artificial resuscitation. If unconscious place in the recovery

position. OBTAIN MEDICAL ATTENTION URGENTLY.

If conscious give plenty of water to drink. Do not induce vomiting. If there is difficulty in breathing give oxygen Ingestion

if available. If breathing stops or shows signs of failing, apply artificial resuscitation. If unconscious place in the recovery position. OBTAIN MEDICAL ATTENTION URGENTLY.

Personal protection for first Wear protective gloves / eye protection.

4.2 Most important symptoms and effects, both acute & delayed.

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed.

No further relevant information available.

Section 5. Fire Fighting

5.1 Extinguishing media

Extinguishing Media Alcohol resistant foam, dry powder, carbon dioxide or vaporising liquid. Use water spray to keep fire exposed

containers cool.

Unsuitable Media Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards Vapour-air mixtures are explosive. Vapours may flow along surfaces to distant ignition sources and flash back.

5.3 Advice for firefighters

Advice for firefighters Evacuate area immediately. Keep up wind. Avoid exposure to toxic vapours and fumes. Fire-fighters should wear

protective clothing and breathing apparatus.

Section 6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal Protection Ensure no sources of ignition. Avoid breathing vapour. Use approved personal protective equipment. Evacuate

area immediately. Do not allow general use of area until it is safe to do so. Beware: vapour is heavier than air and

will tend to accumulate at low spots.

6.2 Environmental precautions

Environmental Keep material out of sewers, storm drains, surface waters and soil. Notify the Environmental Agency and local

Environmental Health Officer if major spillage occurs.

6.3 Methods and material for containment and cleaning up

Major Spillage Contain and absorb on inert material. Transfer absorbent to salvage container for removal. Wash area down with

copious amounts of water.

Minor Spillage Contain and absorb on inert material. Transfer absorbent to container for removal. Allow solvent to evaporate in

remote area, then dispose of absorbent as solid chemical waste. Wash area down with copious amounts of water.

6.4 Reference to other sections

See section 8.2 for information on protective equipment and section 13 for information on disposal.

Section 7. Storage & Handling

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Do not breath vapours. Do not allow to contaminate clothing.

Ensure Local Exhaust Ventilation maintains vapour concentrations below the recommended limits.

7.2 Conditions for safe storage, including any incompatibilities

Well ventilated, cool, dry storage . Protect from direct sun and store away from sources of ignition. Keep containers closed when not in use. Keep well separated from oxidising agents.

7.3 Specific end use(s)

See section 1.2.

Section 8. Workplace Exposure & Personal Protection

8.1 Control parameters

Component	CAS No	Concentration	Workplace Exposure Limits				
			Long Term (8hr TWA)		Short Terr	Short Term 15min period)	
Butylamine	109-73-9	>98%	-	5.0 mg/m-3	-	15.0 mg/m-3	

Exposure data source(s) IOELV: Indicative Occupational Exposure Limit Value.

8.2 Exposure controls

maintained chemical cartridge organic vapour respirator, or use self contained breathing apparatus.

Hand Protection Use solvent resistant gloves.

Eye Protection Use tightly fitting chemical splash proof glasses or goggles.

Skin Protection Avoid contact with skin. If skin contact or contamination of clothing is likely, protective clothing must be worn.

Special Hazards No special precautions required.

Section 9. Physical & Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance Clear colourless liquid.

Odour Pungent fishy odour. Strong ammoniacal odour at higher concentrations.

pH 13 @ 20°C Boiling Point 78°C Melting Point -50°C

Flash Point -9°C (Closed cup)

Upper Flammable Limit
Lower Flammable Limit
Auto Ignition

1.7%
10%
310°C

Explosive Properties Moderate/severe in confined spaces.

Oxidising Properties No.

Vapour Pressure Not applicable

Scientific Laboratory Supplies - Safety Data Sheet Ref: CHE1120 Page 3 of 6

Relative Density 0.7370

Water Solubility Completely miscible in water.

9.2 Other information

No data available.

Section 10. Stability & Reactivity

10.1 Reactivity No data available.

10.2 Chemical Stability Stable under normal conditions

10.3 Possibility of hazardous No data available.

reactions

10.4 Conditions to Avoid Hot surfaces, naked flames or other sources of ignition.

10.5 Incompatable Materials Acids. Strong oxidising agents.

10.6 Hazardous Decomposition Burning will produce toxic fumes of NOx, carbon monoxide and/or carbon dioxide.

Products

Section 11. Toxicological Information

11.1 Information on toxicological effects

Eyes Both the vapour and liquid may, be extremely irritating to eyes and can cause chemical eye burns.

Skin Contact with the liquid may cause burns. May be absorbed through the skin.

LD50 Skin 850mg/kg Rabbit

Ingestion Harmful if swallowed. Causes immediate irritation of the mouth, throat and gastro-intestinal tract.

LD50 Oral 366mg/kg Rat

Inhalation Harmful by inhalation. High concentrations of vapour will produce severe irritation of the eyes, nose, throat and

respiratory tract.

LD50 Inhalation Not available **TCLo** Not available

Carcinogenicity Not considered to be a carcinogen. Mutagenicity Not considered to be a mutagen.

Reproductive Effects None identified.

Section 12. Ecological

12.1 Toxicity A problem material due to it's intense odour. However it is readily biodegraded in the environment.

LC50 Algal Not available LC50 Crustacea Not available LC50 Fish Not available 12.2 Persistence and No data available.

12.3 Bioaccumulative potential No data available. 12.4 Mobility in soil No data available.

Results of PBT & vPvB Assessment not required.

assessment

degradability

None known at present.

12.6 Other adverse effects

Section 13. Disposal Considerations

13.1 Waste treatment methods

Disposal Methods Dispose of in a licensed incinerator for organic solvents. Do not dispose of as domestic waste. Never dispose of

into water courses or sewerage systems due to high risk of explosion.

Contaminated Packaging Use a licensed waste disposer. Do not attempt to burn any residual liquids due to risk of explosion.

Section 14. Transport Information

14.1 UN Number 1125

14.2 Proper Shipping Name n-Butylamine

14.3 Transport classes

UN classification 3 8 Subsidiary hazard(s) Transport category 2 ADR Hazard ID 338 Tunnel Restriction Code D/E

14.4 Packing Group

14.5 Environment hazards See section 12.

14.6 Special precautions for No special precautions required.

14.7 Transport in bulk Not transported in bulk.

Section 15. Regulatory Information

15.1 Safety, health and environment regulations specific for subtance/mixture.

Classification, Labeling & Packaging of Substances & Mixtures Regulations (1272/2008/CE)

Classification Flammable liquid, category 2; Skin corrosion/irritation, category 1A; Acute toxicity, category 4 (oral); Acute

toxicity, category 4 (dermal); Acute toxicity, category 4 (inhalation); Spec target organ tox - single, category 3

Signal word Danger

Hazard Pictograms







Hazard Statements H225, H332, H312, H302, H314, H335

Highly flammable liquid and vapour. Harmful if inhaled. Harmful in contact with skin. Harmful if swallowed.

Causes severe skin burns and eye damage. May cause respiratory irritation.

P210, P280, P305+P351+P338, P302+P352 Precautionary Statements

> Keep away from heat / sparks/open flames/hot surfaces - No smoking. Wear protective gloves / protective clothing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do and continue rinsing. IF ON SKIN: Wash with plenty of soap and water.

15.2 Chemical safety assessment

Assessment not required.

Section 16. Other Information

The information contained in this document only covers the hazards presented by this material, it DOES NOT constitute a workplace risk assessment. See sections 11 for toxicological information and section 12 for ecological information.

Revision number: 1.1 (Supercedes revision 1.0)

Revision date: 16 April 2021

Reviewed by chemist: 16 April 2021

Printed date: 17 August 2022

Copyright: 2022 Scientific Laboratory Supplies