Scientific Laboratory Supplies - Safety Data Sheet

(in accordance with regulation (EU) 2015/830 and regulation (EC) 1272/2008)

Revision: 1.1 Revision date: 16 April 2021 Date printed: 17 August 2022

CHE2782

Section 1. Identification

1.1 Product Identifier CHE2782

Product Name PETROLEUM SPIRIT 100/120 pure 2.5L.

CAS Number 8032-32-4

REACH Registration No 01-2119473851-33-XXXX

1.2 Relevent identified uses of the substance or mixure & uses advised against

Uses of Material Chemical for industrial and laboratory use. Not suitable for domestic use.

1.3 Supplier Scientific Laboratory Supplies

SCIENTIFIC LABORATORY SUPPLIES Wilford Industrial Estate

Ruddington Lane

Wilford Nottingham NG11 7EP

UNITED KINGDOM

Phone 0115 9821111 Fax 0115 9825275

Email sales@scientific-labs.com

1.4 Emergency Telephone (08:00-17:00) 0115 9821111

(24hr) 112 (Have this document to hand)

Section 2. Hazards Identification

2.1 Classification of the substance or mixture

Classification according to regulation 1272/2008/EC

Flammable liquid, category 2 Skin corrosion/irritation, category 2 Reproductive toxicity, category 2 Spec target organ tox - single, category 3

Agnitude hazard autogory 1

Aspiration hazard, category 1

Hazard to aquatic environment, category 2

H225: Highly flammable liquid and vapour.

H315: Causes skin irritation.

H361: Suspected of damaging fertility or the unborn child.

H336: May cause drowsiness or dizziness.

H304: May be fatal if swallowed and enters airways. H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to regulation 1272/2008/EC

Signal word Danger

Hazard Pictograms





Ref: CHE2782





Highly flammable liquid and vapour. Causes skin irritation. May cause drowsiness or dizziness. May be fatal if Hazard Statements

swallowed and enters airways. Toxic to aquatic life with long lasting effects. Suspected of damaging fertility or

the unborn child.

Precautionary Statements Obtain special instructions before use. Keep away from heat / sparks/open flames/hot surfaces - No smoking.

Wear protective gloves / protective clothing / eye protection / face protection. IF exposed or concerned: Get medical advice/attention. Store in a well ventilated place. Keep cool. Avoid release to the environment.

Supplemental Hazard Information (EU)

Repeated exposure may cause skin dryness or cracking.

Section 3. Composition

3.1 Substances

Component	CAS No.	EEC No.	REACH No.	Conc w/w	CLP Classification (1272/2008/CE)
Mixed hydrocarbon solvent	8032-32-4	232-453-7	01-2119473851-33-XXXX	>99.5%	Flam. Liq. 2,Skin Irrit. 2,Repr. 2,STOT SE 3 (D),Asp. Tox.
					1, Aquatic Chronic 2

Section 4. First Aid

4.1 Description of first aid measures

Eyes Irrigate thoroughly with plenty of water for at least 10 minutes, holding the eye open. OBTAIN MEDICAL

Skin Thoroughly wash off skin with soap and water. Remove contaminated clothing immediately and wash before re-

use. In severe cases or if exposure has been great, OBTAIN MEDICAL ATTENTION.

Inhalation Remove from exposure. Keep warm and at rest. If there is difficulty in breathing give oxygen if available. If

breathing stops or shows signs of failing, apply artificial resuscitation. If unconscious place in the recovery position. OBTAIN MEDICAL ATTENTION URGENTLY.

If conscious give plenty of water to drink. Do not induce vomiting. If there is difficulty in breathing give oxygen Ingestion

if available. If breathing stops or shows signs of failing, apply artificial resuscitation. If unconscious place in the recovery position. OBTAIN MEDICAL ATTENTION URGENTLY.

Personal protection for first Wear protective gloves / eye protection.

aiders

4.2 Most important symptoms and effects, both acute & delayed.

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed.

No further relevant information available.

Section 5. Fire Fighting

5.1 Extinguishing media

Extinguishing Media Water spray, foam, dry powder or carbon dioxide. Use water spray to keep fire exposed containers cool.

Unsuitable Media Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards Vapour-air mixtures are explosive.

5.3 Advice for firefighters

Advice for firefighters Evacuate area immediately. Keep up wind. Avoid exposure to toxic vapours and fumes. Fire-fighters should wear

protective clothing and breathing apparatus.

Section 6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal Protection Ensure no sources of ignition. Avoid breathing vapour. Use approved personal protective equipment. Evacuate area immediately. Do not allow general use of area until it is safe to do so. Beware: vapour is heavier than air and

will tend to accumulate at low spots.

6.2 Environmental precautions

Environmental Keep material out of sewers, storm drains, surface waters and soil. Notify the Environmental Agency and local

Environmental Health Officer if major spillage occurs.

6.3 Methods and material for containment and cleaning up

Major Spillage Contain and absorb on inert material. Transfer absorbent to salvage container for removal. Wash area down with

copious amounts of water.

Minor Spillage Contain and absorb on inert material. Transfer absorbent to container for removal. Allow solvent to evaporate in

remote area, then dispose of absorbent as solid chemical waste. Wash area down with copious amounts of water.

6.4 Reference to other sections

See section 8.2 for information on protective equipment and section 13 for information on disposal.

Section 7. Storage & Handling

7.1 Precautions for safe handling

All transfer systems should be earthed to prevent accumulation of static electricity. Avoid contact with skin and eyes. Do not breath vapours. Do not allow to contaminate clothing.

Ensure Local Exhaust Ventilation maintains vapour concentrations below the recommended limits.

7.2 Conditions for safe storage, including any incompatibilities

Well ventilated, cool, dry storage. Protect from direct sun and store away from sources of ignition. Keep containers closed when not in use. Keep well separated from oxidising agents. Large quantities must be stored in accordance with the Petroleum Spirits Act.

7.3 Specific end use(s)

See section 1.2.

Section 8. Workplace Exposure & Personal Protection

8.1 Control parameters

Component	CAS No	Concentration	Workplace Exposure Limits				
			Long Term (8hr TWA)		Short Term 15min period)		
Mixed hydrocarbon solvent	8032-32-4	>99.5%	240.0 ppm	-	-	-	

Exposure data source(s) IOELV: Indicative Occupational Exposure Limit Value.

8.2 Exposure controls

maintained chemical cartridge organic vapour respirator, or use self contained breathing apparatus.

Hand Protection Use solvent resistant gloves.

Skin Protection Avoid contact with skin. If skin contact or contamination of clothing is likely, protective clothing must be worn.

Special Hazards No special precautions required.

Section 9. Physical & Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance Clear colourless liquid.

Odour Characteristic.
pH Not applicable
Boiling Point 102°C
Melting Point -30°C

Flash Point -7°C (Closed cup)

Upper Flammable Limit 8% Lower Flammable Limit 0.9% Auto Ignition 230°C

Explosive Properties Severe in confined spaces.

Oxidising Properties No.

Vapour Pressure 40mmHg @ 20°C

Relative Density 0.7270

Water Solubility Insoluble in water.

9.2 Other information

No data available.

Section 10. Stability & Reactivity

10.1 Reactivity No data available.

10.2 Chemical Stability Stable under normal conditions

10.3 Possibility of hazardous No data available.

reactions

10.4 Conditions to Avoid Hot surfaces, naked flames or other sources of ignition.

10.5 Incompatable Materials Strong oxidising agents.

10.6 Hazardous Decomposition None unusual. Burning will produce smoke, carbon monoxide and/or carbon dioxide.

Products

Section 11. Toxicological Information

11.1 Information on toxicological effects

Eyes Both the vapour and liquid will, act as an eye irritant. Repeated exposure to the vapours can lead to reversible

corneal changes and conjunctivitis

Skin The liquid is mildly irritating to the skin. Repeated or prolonged contact may defat the skin producing irritation

and dermatitis.

LD50 Skin >2920mg/kg Rat

Ingestion Ingestion will cause causes damage to stomach and intestinal linings. May be fatal if swallowed and enters

airways.

LD50 Oral >5840mg/kg Rat

Inhalation Exposure to vapour concentrations above the occupational exposure limits will cause narcosis. Prolonged

exposure to vapour concentrations above the occupational exposure limits will cause headache, nausea, vomiting and irritation of the mucous membranes. High concentrations of vapour may produce central nervous system

depression and unconsciousness.

LD50 Inhalation >23300mg/l Rat (4 hours)

TCLo Not available

Carcinogenicity Not considered to be a carcinogen.

Mutagenicity Not considered to be a mutagen.

Reproductive Effects No information found.

Section 12. Ecological

12.1 Toxicity Moderately toxic to mammals, fish and bacteria.

LC50 Algal 10-30mg/l Algae (72 hours)

LC50 Crustacea 4.6 - 10.0mg/l Daphnia (48 hours)

LC50 Fish 3-10mg/l Fish (96 hours)

12.2 Persistence and

degradability

No data available.

12.3 Bioaccumulative potential No data available.12.4 Mobility in soil No data available.

12.5 Results of PBT & vPvB

assessment

Assessment not required.

12.6 Other adverse effects None known at present.

Scientific Laboratory Supplies - Safety Data Sheet

Ref: CHE2782

Page 4 of 6

Section 13. Disposal Considerations

13.1 Waste treatment methods

Dispose of in a licensed incinerator for organic solvents. Do not dispose of as domestic waste. Never dispose of

into water courses or sewerage systems due to high risk of explosion.

Contaminated Packaging Use a licensed waste disposer. Do not attempt to burn any residual liquids due to risk of explosion.

Section 14. Transport Information

14.1 UN Number 1268

14.2 Proper Shipping Name Petroleum distillates, N.O.S.

14.3 Transport classes

UN classification 3
Subsidiary hazard(s) None
Transport category 2
ADR Hazard ID 33
Tunnel Restriction Code D/E

14.4 Packing Group II

14.5 Environment hazards See section 12.

14.6 Special precautions for No special precautions required.

user

14.7 Transport in bulk Not transported in bulk.

Section 15. Regulatory Information

15.1 Safety, health and environment regulations specific for subtance/mixture.

Classification, Labeling & Packaging of Substances & Mixtures Regulations (1272/2008/CE)

Classification Flammable liquid, category 2; Skin corrosion/irritation, category 2; Reproductive toxicity, category 2; Spec target

organ tox - single, category 3; Aspiration hazard, category 1; Hazard to aquatic environment, category 2

Signal word Danger

Hazard Pictograms









Hazard Statements H225, H315, H336, H304, H411, H361

Highly flammable liquid and vapour. Causes skin irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects. Suspected of damaging fertility or the unborn child.

Precautionary Statements P201, P210, P280, P308+P313, P403+P235, P273

Obtain special instructions before use. Keep away from heat / sparks/open flames/hot surfaces - No smoking. Wear protective gloves / protective clothing / eye protection / face protection. IF exposed or concerned: Get medical advice/attention. Store in a well ventilated place. Keep cool. Avoid release to the environment.

Supplemental Hazard Information (EU) EUH066

Repeated exposure may cause skin dryness or cracking.

15.2 Chemical safety assessment

Assessment not required.

Section 16. Other Information

The information contained in this document only covers the hazards presented by this material, it DOES NOT constitute a workplace risk assessment. See sections 11 for toxicological information and section 12 for ecological information.

Revision number: 1.1 (Supercedes revision 1.0)

Revision date: 16 April 2021

Reviewed by chemist: 16 April 2021

Printed date: 17 August 2022

Copyright: 2022 Scientific Laboratory Supplies