

ID-Nr. 30667-001 Model G90.205.090



Dimensions	
Width (external)	898.00 mm
Depth (external)	615.00 mm
Height (external)	2050.00 mm
Width (internal)	745.00 mm
Depth (internal)	425.00 mm
Height (internal)	1858.00 mm

The available internal dimensions can vary depending on the interior equipment package.

490 kg
752.00 kg/m²
600 kg
75 DN
6 m³/h
66 m³/h
ase have a closer look to EN 14470-2.

Body colour code	RAL 7035
Body colour	light grey
Body surface finish	plain
Door / Drawer colour code	RAL 7035
Door / Drawer colour	light grey
Door / Drawer surface finish	plain

General Information	
Number of doors	2
Door opening angle	180.00°
Depth with open doors	1090 mm
x 50-litre gas cylinders	3 piece
Customs tariff number	94032080

















Gas cylinder cabinet G-ULTIMATE-90 Model G90.205.090, light grey (RAL 7035)

Safe and approved storage of flammable or toxic gases in working areas – for up to 3 x 50-litre gas cylinders

Function / construction:

- No unauthorised use: doors lockable with profile cylinder (integration in an existing locking system possible)
- Easy alignment: adjusting aids to compensate for uneven floor
- Easy mounting of connecting pipes and gas fittings: large interior height (1890 mm), many lead-through possibilities on the top of the cabinet
- **Ventilation:** integrated air ducts ready for connection (DN 75) to a technical exhaust, even ventilation inside the cabinet
- Tested and certified: according to the stricter GS principles

Available equipment:

- Cylinder retainer variable installation in the cabinet, flexibly adjustable in depth, across the entire width of the cabinet
- Comfort interior equipment complete with mounting rails, rolling ramp (L = 350 mm) with pneumatic damper, cylinder retainer and matching tension belts
- Standard interior equipment complete with mounting rails, rolling ramp and cylinder retainer
- Lateral cylinder retainer for two 10-litre cylinders, alternatively in height adjustable version (no tools required)

Front view Side view





