

ID-Nr. 38611-047 Model 1090.195.060.K9.WDC



Dimensions	
Width (external)	599.00 mm
Depth (external)	615.00 mm
Height (external)	1953.00 mm
Width (internal)	450.00 mm
Depth (internal)	522.00 mm
Height (internal)	1647.00 mm
The available internal dimensions can vary depending on the interior equipment package.	

The available internal dimensions can vary depending on the interior equipment package.		
Weight / Load		
Weight without interior equipment	265 kg	
Distributed load	894.00 kg/m²	
Maximum load	600 kg	
Ventilation		
Extraction air	75 DN	
Frequency	50/60 Hz	
Nominal voltage	230 V	
Power consumption in operation	47,5 W	

Outlet strips (Charging power)			
Fuse (1-phase)	16 A		
Power max. (1-phase)	3,68 kW		
Fuse (3-phase)	3 x 16 A		
Power max. (3-phase)	7,36 kW		

Colouring / Surface finish	
Body colour code	RAL 7016
Body colour	anthracite grey
Body surface finish	textured
Door / Drawer colour code	RAL 5010
Door / Drawer colour	gentian blue
Door / Drawer surface finish	textured

General Information	
Number of doors	1
Door opening angle	89.40°
Depth with open doors	1128 mm
Entry width transport base	526 mm
Entry height transport base	90 mm
Customs tariff number	94032080









Safety storage cabinet ION-STORE-90 Model IO90.195.060.K9.WDC

Safe active storage of lithium-ion batteries with integrated alarm system

Function / construction:

- Robust construction and longevity: triple hinged door, safety elements assembled outside the storage compartment for increased protection against corrosion, scratch- and impact-resistant surface, easy to clean
- Easy handling with comfort: smooth doors with permanent self-closing function and oil-dampened door closer; open doors with a minimum amout of force
- No unauthorised use: doors lockable with cylinder locking (integration in an existing locking system possible) and locking state indicator (red/green)
- Easy transport: integrated transport base for internal transportation
- Easy alignment: adjusting aids to compensate for uneven floor
- Ventilation: integrated air ducts ready for connection (DN 75) to a technical exhaust system, spinning wheel in the exhaust grid as an indicator of sufficient technical ventilation
- All-around protection: 90 minute fire protection from outside to inside (type 90 / type tested in accordance with EN 14470-1) and for more than 90 minutes fire resistance for fires from inside to outside

