



## S 10 N - 10 G - ST Dispersing tool

/// Data Sheet

Suitable for dispersing instrument T 10 basic and T 10 standard ST tools are recommended for use with tissue and other fibrous materials\* Working range: 1 - 100 ml Stator diameter: 10 mm Immersion depth: 22 - 100 mm Materials in contact with medium: PTFE, AISI 316L Suitable for solvents Max. temperature: 180 °C Sterilization methods: all methods

www.ika.com





## **Technical Data**

Volume range (H2O) [I]	0.001 - 0.1	
Stator diameter [mm]	10	
Rotor diameter [mm]	7.5	
Gap between rotor and stator [mm]	0.25	
allowable Speed max. [rpm]	30000	
Circumferential speed max. [m/s]	11.8	
Immersion depth [mm]	23 - 100	
Shaft length [mm]	115	
Material in contact with medium	PTFE, AISI 316L	
pH range	2 - 13	
Suitable for solvents	yes	
Suitable for abrasive substances	yes	
Working temperature max. [°C]	180	
Sterilization methods	all methods	
Ultimate fineness, suspensions [µm]	5 - 25	
Ultimate fineness, emulsions [µm]	1 - 10	
Weight [kg]	0.075	
Permissible ambient temperature [°C]	5 - 40	

