Measurement for life.

Product data sheet

MINI THERMO-HUMIDITY METER

Easy to use thermo-humidity meter as part of our range of mini environmental meters.

•

Max min recording and hold function

°C/F selectable measurement units

CE & RoHS/WEEE Compliant

Over range indication

Product features:

- ٠ Dew point and wet bulb temperature measurement
- Humidity level and temperature measurement •
- High accuracy, fast response
- Colour LCD display with backlight
- Low battery indication
- Auto power off enable/disable function ٠
- Supplied with 3 point calibration certificate

Product specifications:

Measurement	Range		Accuracy	Resolution
Humidity:	0 to 100% RH		+/- 3.5%RH between 45 and 75%RH	0.1
			otherwise +/- 4.5%RH	
Temperature:	-20 to +70°C&F		+/- 1.0°C (1.8°F)	0.1
			Dew Point Temp: +/- 1.5°C (2.7°F)*	
			Wet Bulb Temp: +/- 1.5°C (2.7°F)*	
Sampling rate:		2 readings per second		
Power off:		Auto shut down after 15 mins inactivity (unless auto		
		off disa	abled)	
Operating conditions:		-20 to +60°C&F / 10 to 90%RH		
Storage conditions:		-20 to +60°C&F / 10 to 75%RH		
Battery:		3 x AAA (included)		
		Average life - 50 hours on continuous use		
Dimensions:		LCD: 30 x 28mm		
		Net:	168mm x 56mm x 30.5mm	
		Gross	: 247mm x 130mm x 43mm	
Weight:		Meter: 106.5g (including batteries)		
		Paper	: 19g (card, instructions & certificate)	
		Blister	: 37g	
		Gross	: 162.5g	

* Accuracy of dew point temperature is based on environment condition of 25°C / 40 to 100 %RH

Description	Barcode	Product No
Mini thermo-humidity meter	5 011405 134738	13/473/0



View me on the website



Brannar





+44 (0)1946 816600

brannan.co.uk