

# DATA SHEET WEEPRO OVERBOOTS ANTI SLIP SOLE

REF : WL-CBE/AD-00



**FEATURES:** Microporous Film Over boots with anti-slip model. Elasticated top and fixation ties. PVC Anti-slip sole.

**FABRICS AND SEAMS :** White Microporous film 65<sup>GSM</sup> - PVC 370<sup>GSM</sup>- Serged seams

**CERTIFICATION:** Category 3 – TYPE PB 5/6. EN1149-5 : Antistatic fabrics material on the Microporous film. The slip-retardant sole is not antistatic treated.

## PHYSICAL PERFORMANCE

Fabric Physical Properties	Test Method	Résultats	Class
Abrasion resistance	EN530	>400 cycles	Class 4
Flex cracking	ISO 7854 B	>50 000 cycles	Class 6
Trapezoidal Tear	ISO 9073-4	61.5 N / 28.4 N	Class 2
Tensile strength	ISO 13934-1	109 N / 47.4 N	Class 1
Puncture resistance	EN863	9.06 N	Class 1

## FABRIC RESISTANCE TO PENETRATION BY LIQUIDS EN ISO 6530

Fabric Chemical Properties	Penetration	Repellency
Sulphuric Acid 30%	Class 3	Class 3
Sodium Hydroxide 10%	Class 3	Class 3
O-Xylène	Class 3	Class 2
Butan-1-ol	Class 3	Class 3

## CATEGORY 3 TYPE PB: PARTIAL BODY

Dry particles <b>Type PB 5</b> Method as defined by <b>EN ISO 13982-1:2004 + A1:2010</b>	Pass
Light splashes <b>Type PB 6</b> Method as defined by <b>EN 13034 : 2005 +A1: 2009</b>	Pass
Barrier to infective agents <b>EN14126 : 2003</b>	Pass
Protection factor according to <b>EN 1073-2:2002</b>	Class 1
Surface resistivity <b>EN 1149-5</b> / The slip-retardant sole is not antistatic treated.	Pass

## CHART SIZE

Size	WeeSafe reference	LENGHT	WIDTH	Height
<b>XS</b>	WL-CBE/AD-XS	27 CM	11.5 cm	50 CM
<b>SM</b>	WL-CBE/AD-SM	30 CM	11.5 cm	50 CM
<b>LXL</b>	WL-CBE/AD-LXL	36 CM	11.5 cm	50 CM

## PACKAGING

	Units	Weight	Size	Volume
Carton	300	8 KG	60 X 28 X 42 CM	0,0705 M <sup>3</sup>
Pallet	6 000	160 KG	80 X 120 CM	1.41 M <sup>3</sup>

**GENCOD : 3701012801988**

**CUSTOM CODE : 6210109800**

WeeSafe – 1 rue du Centre « Immeuble le Fujy » - 93160 Noisy le Grand Tél : + 33 (0)1 43 09 98 04  
Courriel : [contact@weesafe.fr](mailto:contact@weesafe.fr)