Technical Service Consultants Ltd

Microbiology House, Fir Street, Heywood, Lancashire OL10 1NW, UK T: +44 (0)1706 620600 F: +44 (0)1706 620445

E: sales@tscswabs.co.uk W: www.tscswabs.co.uk

Product Specification Sheet

TS/6-62

PreMoist Swab - Viscose Tip Swab with white shaft for environmental sampling, premoistened in Deionised Water in tube.

Product Code	TS/6-62
Description	PreMoist Swab - Viscose Tip Swab with white shaft for environmental sampling, pre-moistened in Deionised Water in tube.
Intended Use	Environmental sampling, Not suitable for prolonged transport, cleaning validation or hygiene monitoring unless samples are processed on growth media with neutralisers immediately.
Components	Blue cap/ viscose tip swab with polystyrene shaft in polypropylene Tube, Tube Label, hot melt glue, Contents - Deionised water (200 µl)
Contents	De-ionised Water - 1 Litre
Method of Sterilisation	Sterilised by gamma irradiation at dosage of 25-46kGy
Shelf Life	12 months from date of manufacture
Storage Conditions	4-25 °C; in dry and ventilated area; protect from light, heat and moisture in tightly closed original container
Precautions and Limitations	Analyse as soon as possible due to the small volume, so to minimise sample dryout and organism loss. Refrigeration will stabilise recovery of some organisms. Not suitable for most fastidious organism unless analysed immediately.
Pack Size	160 in a box
Other	Quality control testing details on final product: i) Validation of irradiation sterility. ii) Product Appearance.

This specification is intended for guidance only.

You should always refer to a professional with experience in your intended application if in any doubt.

Issue # : 2 Date : 06.06.2016 ProductSpec_TS6-62